


















| | | | | |
|---|--|---|---|--|
| Prüfbericht-Nr.: Test Report No.: | 16072518 001 | Auftrags-Nr.: Order No.: | 174042866 | Seite 1 von 115 Page 1 of 115 |
| Kunden-Referenz-Nr.: Client Reference No.: | N/A | Auftragsdatum: Order date: | 25.11.2015 | |
| Auftraggeber: Client: | Wuxi Sans Electronic Co., Ltd. Industrial WuYi, DongGang Town, Wuxi, Jiangsu, P.R.China | | | |
| Prüfgegenstand: Test item: | Li-ion Battery Charger | | | |
| Bezeichnung / Typ-Nr.: Identification / Type No.: | SSLC084V42J, SSLC058V29J | | | |
| Auftrags-Inhalt: Order content: | GS mark | | | |
| Prüfgrundlage: Test specification: | EN 60335-1:2012+A11:2014 EN 60335-2-29:2004+A2:2010 EN 62233:2008 AfPS GS 2014:01 | | | |
| Wareneingangsdatum: Date of receipt: | 25.11.2015 | Detaillierte Fotodokumentation siehe Anlage zu diesem Bericht Detailed photo documentation see appendix to this report | | |
| Prüfmuster-Nr.: Test sample No.: | A174042866 | | | |
| Prüfzeitraum: Testing period: | 25.11.2015 - 09.03.2016 | | | |
| Ort der Prüfung: Place of testing: | See page 3 | | | |
| Prüflaboratorium: Testing laboratory: | TÜV Rheinland (Guangdong) Ltd. | | | |
| Prüfergebnis*: Test result*: | Pass | | | |
| geprüft von / tested by: | | kontrolliert von / reviewed by: | | |
| <i>2016.03.23</i> | Johnny Cao/Engineer | <i>Johnny Cao</i> | <i>2016.03.28</i> | Dono Zhou/Technical Certifier |
| Datum Date | Name / Stellung Name / Position | Unterschrift Signature | Datum Date | Name / Stellung Name / Position |
| Sonstiges / Other: | | | | |
| The product tested complies with the requirements of the currently harmonized standard under 2006/95/EC as above and complies also with Annex I of 2014/35/EU. Attachment 1: Material list for PAHS risk assessment (1 page) | | | | |
| Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery: | | Prüfmuster vollständig und unbeschädigt Test item complete and undamaged | | |
| * Legende: | 1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n) | 2 = gut 2 = good P(ass) = passed a.m. test specification(s) | 3 = befriedigend 3 = satisfactory F(ail) = entspricht nicht o.g. Prüfgrundlage(n) F(ail) = failed a.m. test specification(s) | 4 = ausreichend 4 = sufficient N/A = nicht anwendbar N/A = not applicable |
| | | | 5 = mangelhaft N/T = nicht getestet 5 = poor N/T = not tested | |
| Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark. | | | | |

| | |
|-----------------------------|--|
| Test item description | Li-ion Battery Charger |
| Trade Mark |  |
| Model/Type reference..... | SSLC084V42J, SSLC058V29J |
| Ratings | AC input: 100-240V, 47-63Hz, 1.8A, DC output: 42V, 2A for SSLC084V42J AC input: 100-240V, 47-63Hz, 1.4A, DC output: 29.4V, 2A for SSLC058V29J |

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBS that own these marks.

| | |
|---|--|
|  SANS ELECTRONIC CO., LTD |  SANS ELECTRONIC CO., LTD |
| Li-ion Battery Charger MODEL : SSLC084V42J INPUT : AC100V-240V~1.8A MAX 47-63Hz OUTPUT : 42.0V --- 2.0A  | Li-ion Battery Charger MODEL : SSLC058V29J INPUT : AC100V-240V~1.4A MAX 47-63Hz OUTPUT : 29.4V --- 2.0A  |
|     |     |
|  |  |
| ● CHARGING ● CHARGE-FULL OR DISCONNECT | ● CHARGING ● CHARGE-FULL OR DISCONNECT |
|  <p>CAUTION : TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK) . NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.</p> <p>BEFORE CHARGING READ THE INSTRUCTIONS! FOR INDOOR USE, OR DO NOT EXPOSE TO RAIN</p> |  <p>CAUTION : TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK) . NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.</p> <p>BEFORE CHARGING READ THE INSTRUCTIONS! FOR INDOOR USE, OR DO NOT EXPOSE TO RAIN</p> |
| MADE IN CHINA Manufacturer: Wuxi Sans Electronic Co., Ltd. Address: Industrial WuYi, DongGang Town, Wuxi, Jiangsu, P. R. China | MADE IN CHINA Manufacturer: Wuxi Sans Electronic Co., Ltd. Address: Industrial WuYi, DongGang Town, Wuxi, Jiangsu, P. R. China |

Remarks: ID 1419033385

Summary of testing:

1. The samples are tested and found to be complied with the requirements of standards listed on cover page
2. Full tests have been carried out on model SSLC084V42J, SSLC058V29J.
3. For EMF requirements, all required tests have been performed and passed. Please refer to page 115.
4. The appliances were tested according European harmonized standards.
5. Testing location: Waltek Services (Foshan) Co., Ltd
2/F,2nd Building, Sunlink International Machinery City, Chencun Town, Shunde District, Foshan
528313,Guangdong,P.R.China.


| | |
|---|---|
| Test item particulars | |
| Classification of installation and use | Portable appliance and household indoor use |
| Supply Connection..... | Power cord with a non-detachable plug, Type Y |
| | |
| | |
| Possible test case verdicts: | |
| - test case does not apply to the test object..... | N/A |
| - test object does meet the requirement | P (Pass) |
| - test object does not meet the requirement | F (Fail) |
| Testing | |
| Date of receipt of test item | 25.11.2015 |
| Date (s) of performance of tests | 25.11.2015 to 09.03.2016 |
| General remarks: | |
| <p>The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.</p> <p>Throughout this report a point is used as the decimal separator.</p> <ol style="list-style-type: none"> Construction for all alternative components listed in table 24.1 was considered in this report. The requirements of AfPS GS 2014:01 have been considered in this report. The risk analysis, categorization and evaluation indicate that the product complies to AfPS GS 2014:01. For PAHs requirements, see material list for PAH risk assessment for detail. EN 60335-1:2012/AC:2014 is considered and passed. All relevant EK-decisions have been considered. Foreseeable use was considered. Currently neither a safeguard clause procedure has been invoked nor is an increase in accidents known for this/these product(s). Factory: Wuxi Sans Electronic Co.,Ltd Industrial WuYi, DongGang Town, Wuxi, Jiangsu, P.R.China | |

General product information:

1. The appliance is class I appliance and for household use only.
2. The differences between the two models are listed as below table A.

Table A:

| No. | Model | Input Voltage (V) | Rated frequency (Hz) | Input current (A) | Rated Output Voltage (V) | Rated Output Current (A) | Difference |
|-----|-------------|-------------------|----------------------|-------------------|--------------------------|--------------------------|----------------|
| 1 | SSLC084V42J | AC100-240V | 47-63Hz | 1.8A | DC42V | 2A | Output circuit |
| 2 | SSLC058V29J | AC100-240V | 47-63Hz | 1.4A | DC29.4V | 2A | |

| IEC 60335-2-29 | | | |
|-----------------------|--|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5 | GENERAL CONDITIONS FOR THE TESTS | | P |
| | Tests performed according to clause 5, e.g. nature of supply, sequence of testing, etc. | | P |
| 5.2 | If the test of 21.101 is carried out two additional battery chargers required (IEC 60335-2-29) | | P |
| 5.101 | Battery chargers tested as motor-operated appliances (IEC 60335-2-29) | | P |
| 6 | CLASSIFICATION | | P |
| 6.1 | Protection against electric shock: Class 0, 0I, I, II, III.....: | Class I | P |
| 6.2 | Protection against harmful ingress of water | | N/A |
| 7 | MARKING AND INSTRUCTIONS | | P |
| 7.1 | Rated voltage or voltage range (V).....: | 100-240 | P |
| | Symbol for nature of supply, or.....: | ~ | P |
| | Rated frequency (Hz) | 47-63Hz | P |
| | Rated power input (W), or | | N/A |
| | Rated current (A) | See rating label on page 6 | P |
| | Manufacturer's or responsible vendor's name, trademark or identification mark.....: |  | P |
| | Model or type reference.....: | See rating label on page 6 | P |
| | Symbol IEC 60417-5172, for class II appliances | | N/A |
| | IP number, other than IPX0.....: | | N/A |
| | Symbol IEC 60417-5180, for class III appliances, unless | | N/A |
| | the appliance is operated by batteries only | | N/A |
| | Symbol IEC 60417-5036, for the enclosure of electrically-operated water valves in external hose-sets for connection of an appliance to the water mains, if the working voltage exceeds extra-low voltage | | N/A |
| | Battery chargers marked with (IEC 60335-2-29): | | P |
| | - rated d.c. output voltage (V) | | P |
| | - rated d.c. output current (A) | | P |
| | - rated current (A) of protective devices incorporated in a d.c. distribution board | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|---------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - polarity of the output terminals indicated by symbol IEC 60417-5005 for the positive terminal and IEC 60417-5006 for the negative terminal (IEC 60335-2-29/A2) | See in rating label | P |
| | - time-current characteristic of fuse-links of the time-lag type | | P |
| | If the output exceeds 20 VA, battery chargers marked with (IEC 60335-2-29): | | P |
| | - before charging, read the instructions | | P |
| | - for indoor use or do not expose to rain, unless appliance is at least IPX4 | | P |
| | If the output exceeds 20 VA and the battery charger is for lead-acid batteries, battery chargers marked with (IEC 60335-2-29): | | N/A |
| | - disconnect the supply before making or breaking the connections to the battery | | N/A |
| | - WARNING: Explosive gases. Prevent flames and sparks. Provide adequate ventilation during charging. | | N/A |
| | Battery chargers incorporating an engine cranking switch allowing the charger to supply a supplementary starting current for the engine marked with (IEC 60335-2-29): | | N/A |
| | - maximum "on" time | | N/A |
| | - minimum "off" time or maximum ratio between "on" time and "off" time | | N/A |
| 7.2 | Warning for stationary appliances for multiple supply | | N/A |
| | Warning placed in vicinity of terminal cover | | N/A |
| 7.3 | Range of rated values marked with the lower and upper limits separated by a hyphen | | P |
| | Different rated values marked with the values separated by an oblique stroke | | N/A |
| 7.4 | Appliances adjustable for different rated voltages, the voltage setting is clearly discernible | | N/A |
| | Requirement met if frequent changes are not required and the rated voltage to which the appliance is to be adjusted is determined from a wiring diagram | | N/A |
| | Output voltage clearly discernible if the battery charger can be adjusted to different rated d.c. output voltages (IEC 60335-2-29) | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 7.5 | Appliances with more than one rated voltage or one or more rated voltage ranges, marked with rated input or rated current for each rated voltage or range, unless | | P |
| | the power input is related to the arithmetic mean value of the rated voltage range | | N/A |
| | Relation between marking for upper and lower limits of rated power input or rated current and voltage is clear | | P |
| 7.6 | Correct symbols used | | P |
| | Symbol for nature of supply placed next to rated voltage | | P |
| | Symbol for class II appliances placed unlikely to be confused with other marking | | N/A |
| | Units of physical quantities and their symbols according to international standardized system | | P |
| 7.7 | Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply, unless | | N/A |
| | correct mode of connection is obvious | | N/A |
| 7.8 | Except for type Z attachment, terminals for connection to the supply mains indicated as follows: | | N/A |
| | - marking of terminals exclusively for the neutral conductor (letter N) | | N/A |
| | - marking of protective earthing terminals (symbol IEC 60417-5019) | | N/A |
| | - marking not placed on removable parts | | N/A |
| 7.9 | Marking or placing of switches which may cause a hazard | | N/A |
| 7.10 | Indications of switches on stationary appliances and controls on all appliances by use of figures, letters or other visual means | No such part | N/A |
| | This applies also to switches which are part of a control | | N/A |
| | If figures are used, the off position indicated by the figure 0 | | N/A |
| | The figure 0 indicates only OFF position, unless no confusion with the OFF position | | N/A |
| 7.11 | Indication for direction of adjustment of controls | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 7.12 | Instructions for safe use provided | | P |
| | Details concerning precautions during user maintenance | | P |
| | The instructions state that: | | P |
| | - the appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction | | P |
| | - children being supervised not to play with the appliance | | P |
| | Instructions for safe use contains (IEC 60335-2-29): | | P |
| | - specification of types, number of cells and rated capacity of batteries that can be charged | | P |
| | - warning against recharging non-rechargeable batteries | | P |
| | - statement that during charging, batteries must be placed in the well-ventilated area, only for battery chargers for lead-acid batteries | | N/A |
| | - statement that battery chargers must only be plugged into an earthed socket-outlet, only for portable Class I battery chargers for outdoor use | | N/A |
| | - explanation of automatic function stating any limitation, only for automatic battery chargers | | N/A |
| | Battery chargers for charging automobile batteries include substance concerning (IEC 60335-2-29): | | N/A |
| | - The battery terminal not connected to the chassis has to be connected first. The other connection is to be made to the chassis, remote from the battery and fuel line. The battery charger is then to be connected to the supply mains; | | N/A |
| | - After charging, disconnect the battery charger from the supply mains. Then remove the chassis connection and then the battery connection. | | N/A |
| | For a part of class III construction supplied from a detachable power supply unit, the instructions state that the appliance is only to be used with the unit provided | | N/A |
| | Instructions for class III appliances state that it must only be supplied at SELV, unless | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | it is a battery-operated appliance, the battery being charged outside the appliance | | N/A |
| 7.12.1 | Sufficient details for installation supplied | | P |
| | For an appliance intended to be permanently connected to the water mains and not connected by a hose-set, this is stated | | N/A |
| | The instructions for battery chargers for installation in caravans and similar vehicles shall state that the connection to the supply mains is to be in accordance with the national wiring rules (IEC 60335-2-29). | | N/A |
| 7.12.2 | Stationary appliances not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III, the instructions state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules | | N/A |
| 7.12.3 | Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions state that the fixed wiring must be protected | | N/A |
| 7.12.4 | Instructions for built-in appliances: | | N/A |
| | - dimensions of space | | N/A |
| | - dimensions and position of supporting and fixing | | N/A |
| | - minimum distances between parts and surrounding structure | | N/A |
| | - minimum dimensions of ventilating openings and arrangement | | N/A |
| | - connection to supply mains and interconnection of separate components | | N/A |
| | - allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring, unless | | N/A |
| | a switch complying with 24.3 | | N/A |
| 7.12.5 | Replacement cord instructions, type X attachment with a specially prepared cord | | N/A |
| | Replacement cord instructions, type Y attachment | | N/A |
| | Replacement cord instructions, type Z attachment | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|--------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 7.12.6 | Caution in the instructions for appliances incorporating a non-self-resetting thermal cut-out that is reset by disconnection of the supply mains, if this cut-out is required to comply with the standard | | N/A |
| 7.12.7 | Instructions for fixed appliances stating how the appliance is to be fixed | | N/A |
| 7.12.8 | Instructions for appliances connected to the water mains: | | N/A |
| | - max. inlet water pressure (Pa) | | N/A |
| | - min. inlet water pressure, if necessary (Pa) | | N/A |
| | Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets | | N/A |
| 7.13 | Instructions and other texts in an official language | English and German | P |
| 7.14 | Marking clearly legible and durable, rubbing test as specified | | P |
| 7.15 | Markings on a main part | | P |
| | Marking clearly discernible from the outside, if necessary after removal of a cover | | P |
| | For portable appliances, cover can be removed or opened without a tool | | N/A |
| | For stationary appliances, name, trademark or identification mark and model or type reference visible after installation | | N/A |
| | For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions | | N/A |
| | Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading | | N/A |
| 7.16 | Marking of a possible replaceable thermal link or fuse link clearly visible with regard to replacing the link | | N/A |
| 7.101 | D.C. distribution boards marked with (IEC 60335-2-29): | | N/A |
| | - maximum output current (A) for each output circuit..... | | N/A |
| | - types of any additional power supply which can be connected | | N/A |
| 8 | PROTECTION AGAINST ACCESS TO LIVE PARTS | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 8.1 | Adequate protection against accidental contact with live parts | | P |
| 8.1.1 | Requirement applies for all positions, detachable parts removed | | P |
| | Lamps behind a detachable cover not removed, if conditions met | | N/A |
| | Insertion or removal of lamps, protection against contact with live parts of the lamp cap | | N/A |
| | Use of test probe B of IEC 61032, with a force not exceeding 1 N: no contact with live parts | | P |
| | Use of test probe B of IEC 61032 through openings, with a force of 20N: no contact with live parts | | P |
| 8.1.2 | Use of test probe 13 of IEC 61032, with a force not exceeding 1 N, through openings in class 0 appliances and class II appliances/constructions: no contact with live parts | | P |
| | Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts | | N/A |
| 8.1.3 | For appliances other than class II, use of test probe 41 of IEC 61032, with a force not exceeding 1 N: no contact with live parts of visible glowing heating elements | | N/A |
| 8.1.4 | Accessible part not considered live if: | | P |
| | - safety extra-low a.c. voltage: peak value not exceeding 42,4 V | | N/A |
| | - safety extra-low d.c. voltage: not exceeding 42,4 V | | P |
| | - or separated from live parts by protective impedance | | P |
| | If protective impedance: d.c. current not exceeding 2 mA, and | | N/A |
| | a.c. peak value not exceeding 0,7 mA | | P |
| | - for peak values over 42,4 V up to and including 450 V, capacitance not exceeding 0,1 µF | | N/A |
| | - for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 µC | | P |
| | - for peak values over 15kV, the energy in the discharge not exceeding 350 mJ | | N/A |
| 8.1.5 | Live parts protected at least by basic insulation before installation or assembly: | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - built-in appliances | | N/A |
| | - fixed appliances | | N/A |
| | - appliances delivered in separate units | | N/A |
| 8.2 | Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only | | P |
| | Only possible to touch parts separated from live parts by double or reinforced insulation | | P |
| 9 | STARTING OF MOTOR-OPERATED APPLIANCES | | N/A |
| | Requirements and tests are specified in part 2 when necessary | | N/A |
| 10 | POWER INPUT AND CURRENT | | P |
| 10.1 | Power input at normal operating temperature, rated voltage and normal operation not deviating from rated power input by more than shown in table 1 ..: | | N/A |
| | Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless | | N/A |
| | the rated power input is related to the arithmetic mean value | | N/A |
| 10.2 | Current at normal operating temperature, rated voltage and normal operation not deviating from rated current by more than shown in table 2 | (see appended table) | P |
| | Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless | | P |
| | the rated current is related to the arithmetic mean value of the range | | N/A |
| 10.101 | No-load d.c. output voltage does not exceed 42,2 V (IEC 60335-2-29).....: | (see appended table) | P |
| 10.102 | Arithmetic mean value of output current does not deviate from rated d.c. output current by more than 10 % (IEC 60335-2-29) | (see appended table) | P |
| 11 | HEATING | | P |
| 11.1 | No excessive temperatures in normal use | | P |
| 11.2 | The appliance is held, placed or fixed in position as described | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Battery chargers are placed in the test corner as specified for heating appliances (IEC 60335-2-29) | | P |
| 11.3 | Temperature rises, other than of windings, determined by thermocouples | | P |
| | Temperature rises of windings determined by resistance method, unless | | N/A |
| | the windings are non-uniform or it is difficult to make the necessary connections | | N/A |
| 11.4 | Heating appliances operated under normal operation at 1,15 times rated power input (W) | | N/A |
| 11.5 | Battery chargers are only supplied at 1,06 times rated voltage (IEC 60335-2-29) | (see appended table) | P |
| 11.6 | Combined appliances operated under normal operation at most unfavourable voltage between 0,94 and 1,06 times rated voltage (V) | | N/A |
| 11.7 | Battery chargers are operated until steady conditions are established (IEC 60335-2-29) | | P |
| 11.8 | Temperature rises monitored continuously and not exceeding the values in table 3 | (see appended table) | P |
| | If the temperature rise of a motor winding exceeds the value of table 3, or | | N/A |
| | if there is doubt with regard to classification of insulation, | | N/A |
| | tests of Annex C are carried out | | N/A |
| | Sealing compound does not flow out | | P |
| | Protective devices do not operate, except | | P |
| | components in protective electronic circuits tested for the number of cycles specified in 24.1.4 | | N/A |
| 13 | LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE | | P |
| 13.1 | Leakage current not excessive and electric strength adequate | | P |
| | Heating appliances operated at 1,15 times the rated power input (W) | | N/A |
| | Motor-operated appliances and combined appliances supplied at 1,06 times the rated voltage (V) | (see appended table) | P |
| | Protective impedance and radio interference filters disconnected before carrying out the tests | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 13.2 | For class 0, class II and class III appliances, leakage current measured by means of the circuit described in figure 4 of IEC 60990 | | N/A |
| | For other appliances, a low impedance ammeter may be used | | P |
| | Leakage current measurements | (see appended table) | P |
| 13.3 | The appliance is disconnected from the supply | | P |
| | Electric strength tests according to table 4..... | (see appended table) | P |
| | No breakdown during the tests | | P |
| 14 | TRANSIENT OVERVOLTAGES | | N/A |
| | Appliances withstand the transient over-voltages to which they may be subjected | | N/A |
| | Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6 | | N/A |
| | No flashover during the test, unless | | N/A |
| | of functional insulation if the appliance complies with clause 19 with the clearance short-circuited | | N/A |
| 15 | MOISTURE RESISTANCE | | P |
| 15.1 | Enclosure provides the degree of moisture protection according to classification of the appliance | | N/A |
| | Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3 | | N/A |
| | No trace of water on insulation which can result in a reduction of clearances or creepage distances below values specified in clause 29 | | N/A |
| 15.1.1 | Appliances, other than IPX0, subjected to tests as specified in IEC 60529..... | | N/A |
| | Water valves containing live parts in external hoses for connection of an appliance to the water mains tested as specified for IPX7 appliances | | N/A |
| 15.1.2 | Hand-held appliance turned continuously through the most unfavourable positions during the test | | N/A |
| | Built-in appliances installed according to the instructions | | N/A |
| | Appliances placed or used on the floor or table placed on a horizontal unperforated support | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board | | N/A |
| | For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube | | N/A |
| | For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube, and | | N/A |
| | for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube | | N/A |
| | Wall-mounted appliances, take into account the distance to the floor stated in the instructions | | N/A |
| | Appliances normally fixed to a ceiling are mounted underneath a horizontal unperforated support, the pivot axis of the oscillating tube located at the level of the underside of the support, and | | N/A |
| | for IPX4 appliances, the movement of the tube is limited to two times 90° from the vertical for a period of 5 min | | N/A |
| | Appliances with type X attachment fitted with a flexible cord as described | | N/A |
| | Detachable parts subjected to the relevant treatment with the main part | | N/A |
| | However, if a part has to be removed for user maintenance and a tool is needed, this part is not removed | | N/A |
| 15.2 | Spillage of liquid does not affect the electrical insulation | | N/A |
| | Appliances with type X attachment fitted with a flexible cord as described | | N/A |
| | Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable | | N/A |
| | Detachable parts are removed | | N/A |
| | Overfilling test with additional amount of water, over a period of 1 min (l).....: | | N/A |
| | The appliance withstands the electric strength test of 16.3 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | No trace of water on insulation that can result in a reduction of clearances or creepage distances below values specified in clause 29 | | N/A |
| 15.3 | Appliances proof against humid conditions | | P |
| | Checked by test Cab: Damp heat steady state in IEC 60068-2-78 | | P |
| | Detachable parts removed and subjected, if necessary, to the humidity test with the main part | | P |
| | Humidity test for 48 h in a humidity cabinet | 25°C, 93% R.H. | P |
| | Reassembly of those parts that may have been removed | | P |
| | The appliance withstands the tests of clause 16 | | P |
| 16 | LEAKAGE CURRENT AND ELECTRIC STRENGTH | | P |
| 16.1 | Leakage current not excessive and electric strength adequate | | P |
| | Protective impedance disconnected from live parts before carrying out the tests | | P |
| | Tests carried out at room temperature and not connected to the supply | | P |
| 16.2 | Single-phase appliances: test voltage 1,06 times rated voltage (V) | (see appended table) | P |
| | Three-phase appliances: test voltage 1,06 times rated voltage divided by $\sqrt{3}$ (V) | | N/A |
| | Leakage current measurements | (see appended table) | P |
| | Limit values doubled if: | | — |
| | - all controls have an off position in all poles, or | | N/A |
| | - the appliance has no control other than a thermal cut-out, or | | N/A |
| | - all thermostats, temperature limiters and energy regulators do not have an off position, or | | N/A |
| | - the appliance has radio interference filters | | N/A |
| | With the radio interference filters disconnected, the leakage current do not exceed limits specified | | N/A |
| 16.3 | Electric strength tests according to table 7..... | (see appended table) | P |
| | Test voltage applied between the supply cord and inlet bushing and cord guard and cord anchorage as specified | (see appended table) | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|----------------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | No breakdown during the tests | | P |
| 17 | OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS | | P |
| | No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use | (see appended table) | P |
| | Appliance supplied with 1,06 or 0,94 times rated voltage under the most unfavourable short-circuit or overload likely to occur in normal use (V) | 1.06 x 240V = 254.4V | P |
| | Output terminals of battery chargers are short-circuited (IEC 60335-2-29) | | P |
| | Basic insulation is not short-circuited | | P |
| | Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K | | P |
| | Temperature of the winding not exceeding the value specified in table 8 | | P |
| | However, limits do not apply to fail-safe transformers complying with sub-clause 15.5 of IEC 61558-1 | | N/A |
| 18 | ENDURANCE | | N/A |
| | Requirements and tests are specified in part 2 when necessary | | N/A |
| 19 | ABNORMAL OPERATION | | P |
| 19.1 | The risk of fire, mechanical damage or electric shock under abnormal or careless operation obviated | | P |
| | Electronic circuits so designed and applied that a fault will not render the appliance unsafe | (see appended table) | P |
| | if the appliance also has a control that limit the temperature during clause 11 it is subjected to the test of 19.4, and | | N/A |
| | Appliances incorporating motors subjected to the tests of 19.7 to 19.10, as applicable | | N/A |
| | Appliances incorporating electronic circuits subjected to the tests of 19.11 and 19.12, as applicable | | P |
| | Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 19.2 | Test of appliances with heating elements with restricted heat dissipation; test voltage (V), power input of 0.85 times rated power input (W) | | N/A |
| 19.3 | Test of 19.2 repeated; test voltage (V), power input of 1,24 times rated power input (W) | | N/A |
| 19.4 | Test conditions as in clause 11, any control limiting the temperature during tests of clause 11 short-circuited | | N/A |
| 19.5 | Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the sheath | | N/A |
| | The test repeated with reversed polarity and the other end of the heating element connected to the sheath | | N/A |
| | The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4 | | N/A |
| 19.6 | Appliances with PTC heating elements tested at rated voltage, establishing steady conditions | | N/A |
| | The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures (V) | | N/A |
| 19.7 | Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque, or | | N/A |
| | locking moving parts of other appliances | | N/A |
| | Locked rotor, capacitors open-circuited one at a time | | N/A |
| | Test repeated with capacitors short-circuited one at a time, unless | | N/A |
| | capacitor is of class P2 of IEC 60252-1 | | N/A |
| | Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed | | N/A |
| | Other appliances supplied with rated voltage for a period as specified | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Winding temperatures not exceeding values specified in table 8.....: | | N/A |
| 19.8 | Multi-phase motors operated at rated voltage with one phase disconnected | | N/A |
| 19.9 | Running overload test on appliances incorporating motors intended to be remotely or automatically controlled or liable to be operated continuously | | N/A |
| | Motor-operated and combined appliances for which 30.2.3 is applicable and that use overload protective devices relying on electronic circuits to protect the motor windings, are also subjected to the test | | N/A |
| | Winding temperatures not exceeding values as specified | | N/A |
| 19.10 | Series motor operated at 1,3 times rated voltage for 1 min (V) | | N/A |
| | During the test, parts not being ejected from the appliance | | N/A |
| 19.11 | Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless | | P |
| | they comply with the conditions specified in 19.11.1 | | N/A |
| | Appliances incorporating an electronic circuit that relies upon a programmable component to function correctly, subjected to the test of 19.11.4.8, unless | | N/A |
| | restarting does not result in a hazard | | N/A |
| | Appliances having a device with an off position obtained by electronic disconnection, or a device placing the appliance in a stand-by mode, subjected to the tests of 19.11.4 | | N/A |
| | If the safety of the appliance under any of the fault conditions depends on the operation of a miniature fuse-link complying with IEC 60127, the test of 19.12 is carried out | | P |
| | During and after each test the following is checked: | | P |
| | - the temperature of the windings do not exceed the values specified in table 8 | | P |
| | - the appliance complies with the conditions specified in 19.13 | | P |
| | - any current flowing through protective impedance not exceeding the limits specified in 8.1.4 | | P |

| IEC 60335-2-29 | | | |
|----------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided both of the following conditions are met: | | — |
| | - the base material of the printed circuit board withstands the test of Annex E | | N/A |
| | - any loosened conductor does not reduce clearance or creepage distances between live parts and accessible metal parts below the values specified in clause 29 | | N/A |
| 19.11.1 | Fault conditions a) to g) in 19.11.2 are not applied to circuits or parts of circuits meeting both of the following conditions: | | — |
| | - the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified | | N/A |
| | - the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction of other parts of the appliance does not rely on the correct functioning of the electronic circuit | | P |
| 19.11.2 | Fault conditions applied one at a time, the appliance operating under conditions specified in clause 11, but supplied at rated voltage, duration of the tests as specified: | | — |
| | a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in clause 29 | | P |
| | b) open circuit at the terminals of any component | | P |
| | c) short circuit of capacitors, unless | | P |
| | they comply with IEC 60384-14 | | P |
| | d) short circuit of any two terminals of an electronic component, other than integrated circuits | | P |
| | This fault condition is not applied between the two circuits of an optocoupler | | P |
| | e) failure of triacs in the diode mode | | P |
| | f) failure of microprocessors and integrated circuits | | P |
| | g) failure of an electronic power switching device | | N/A |
| | Each low power circuit is short-circuited by connecting the low-power point to the pole of the supply source from which the measurements were made | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 19.11.3 | If the appliance incorporates a protective electronic circuit which operates to ensure compliance with clause 19, the relevant test is repeated with a single fault simulated, as indicated in a) to g) of 19.11.2 | | N/A |
| 19.11.4 | Appliances having a device with an off position obtained by electronic disconnection, or | | N/A |
| | a device that can be placed in the stand-by mode, | | N/A |
| | subjected to the tests of 19.11.4.1 to 19.11.4.7, the device being set in the off position or in the stand-by mode | | N/A |
| | Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.4.1 to 19.11.4.7, the tests being carried out after the protective electronic circuit has operated, except that | | N/A |
| | appliances operated for 30 s or 5 min during the test of 19.7 are not subjected to the tests for electromagnetic phenomena. | | N/A |
| | Surge protective devices disconnected, unless | | N/A |
| | They incorporate spark gaps | | N/A |
| 19.11.4.1 | The appliance is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4 | | N/A |
| 19.11.4.2 | The appliance is subjected to radiated fields in accordance with IEC 61000-4-3, test level 3 | | N/A |
| 19.11.4.3 | The appliance is subjected to fast transient bursts in accordance with IEC 61000-4-4, test level 3 or 4 as specified | | N/A |
| 19.11.4.4 | The power supply terminals of the appliance subjected to voltage surges in accordance with IEC 61000-4-5, test level 3 or 4 as specified | | N/A |
| | Earthed heating elements in class I appliances disconnected | | N/A |
| 19.11.4.5 | The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3 | | N/A |
| 19.11.4.6 | Appliances having a rated current not exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-11 | | N/A |
| | Appliances having a rated current exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-34 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|---------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 19.11.4.7 | The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2 | | N/A |
| 19.11.4.8 | The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduced to a level such that the appliance ceases to respond or parts controlled by the programmable component cease to operate | | N/A |
| | The appliance continues to operate normally, or | | N/A |
| | requires a manual operation to restart | | N/A |
| 19.12 | If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A).....: | Rated 3.15A, measured 18A | P |
| 19.13 | During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts | | P |
| | Temperature rises not exceeding the values shown in table 9 | (see appended table) | P |
| | During the tests, the values of Table 8 apply (IEC 60335-2-29) | | P |
| | Compliance with clause 8 not impaired | | P |
| | No rupture of the battery (IEC 60335-2-29/A2) | | P |
| | If the appliance can still be operated it complies with 20.2 | | N/A |
| | Insulation, other than of class III appliances or class III constructions that do not contain live parts, withstands the electric strength test of 16.3, the test voltage as specified in table 4: | | N/A |
| | - basic insulation (V) | (see appended table) | P |
| | - supplementary insulation (V).....: | | N/A |
| | - reinforced insulation (V) | (see appended table) | P |
| | After operation or interruption of a control, clearances and creepage distances across the functional insulation withstand the electric strength test of 16.3, the test voltage being twice the working voltage | | P |
| | The appliance does not undergo a dangerous malfunction, and | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|--|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | no failure of protective electronic circuits, if the appliance is still operable | | P |
| | Appliances tested with an electronic switch in the off position, or in the stand-by mode: | | N/A |
| | - do not become operational, or | | N/A |
| | - if they become operational, do not result in a dangerous malfunction during or after the tests of 19.11.4 | | N/A |
| | If the appliance contains lids or doors that are controlled by one or more interlocks, one of the interlocks may be released provided that: | | N/A |
| | - the lid or door does not move automatically to an open position when the interlock is released, and | | N/A |
| | - the appliance does not start after the cycle in which the interlock was released | | N/A |
| 19.14 | Appliances operated under the conditions of clause 11, any contactor or relay contact operating under the conditions of clause 11 being short-circuited | | N/A |
| | For a relay or contactor with more than one contact, all contacts are short-circuited at the same time | | N/A |
| | A relay or contactor operating only to ensure the appliance is energized for normal use is not short-circuited | | N/A |
| | If more than one relay or contactor operates in clause 11, they are short-circuited in turn | | N/A |
| 19.15 | For appliances with a mains voltage selector switch, the switch is set to the lowest rated voltage position and the highest value of rated voltage is applied | | N/A |
| 19.101 | Battery chargers supplied at rated voltage and operated under normal operation, any control limiting the temperature during tests of clause 11 short-circuited (IEC 60335-2-29) | | N/A |
| 19.102 | Reverse connection of battery chargers to a fully charged battery at rated voltage (IEC 60335-2-29) | Incorrect polarity connection is prevented | P |
| | The capacity of the battery (IEC 60335-2-29) | | N/A |
| 19.103 | Battery chargers intended to be used with a d.c. distribution board supplied at rated voltage and operated under normal operation, load increased as specified until protective device operates or short-circuit conditions are established (IEC 60335-2-29) | | N/A |
| 20 | STABILITY AND MECHANICAL HAZARDS | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|-------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 20.1 | Appliances having adequate stability | | P |
| | Tilting test through an angle of 10°, appliance placed on an inclined plane/horizontal support, not connected to the supply mains; appliance does not overturn | | P |
| | Tilting test repeated on appliances with heating elements, angle of inclination increased to 15° | | N/A |
| | Possible heating test in overturned position; temperature rise does not exceed values shown in table 9 | | N/A |
| 20.2 | Moving parts adequately arranged or enclosed as to provide protection against personal injury | | N/A |
| | Protective enclosures, guards and similar parts are non-detachable, and | | N/A |
| | have adequate mechanical strength | | N/A |
| | Enclosures that can be opened by overriding an interlock are considered to be detachable parts | | N/A |
| | Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard by unexpected closure | | N/A |
| | Not possible to touch dangerous moving parts with the test probe described | | N/A |
| 21 | MECHANICAL STRENGTH | | P |
| 21.1 | Appliance has adequate mechanical strength and is constructed as to withstand rough handling | | P |
| | Checked by applying 3 blows to every point of the enclosure like to be weak, in accordance with test Ehb of IEC 60068-2-75, spring hammer test, with an impact energy of 1,0 J ± 0,05 J (IEC 60335-2-29) | Plastic enclosure | P |
| | The appliance shows no damage impairing compliance with this standard, and | | P |
| | compliance with 8.1, 15.1 and clause 29 not impaired | | P |
| | If doubt, supplementary or reinforced insulation subjected to the electric strength test of 16.3 | | N/A |
| | If necessary, repetition of groups of three blows on a new sample | | N/A |
| 21.2 | Accessible parts of solid insulation having strength to prevent penetration by sharp implements | | P |

| IEC 60335-2-29 | | | |
|----------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Test not applicable if the thickness of supplementary insulation is at least 1 mm and reinforced insulation at least 2 mm | | P |
| | The insulation is tested as specified, and does withstand the electric strength test of 16.3 | | N/A |
| 21.101 | Battery chargers, other than built-in battery chargers, having a mass not exceeding 5 kg, subjected to a drop test (IEC 60335-2-29) | | P |
| | Battery chargers show no damage that could impair compliance with 8.1, 15.1.1, 16.3 and cl. 29 (IEC 60335-2-29) | | P |
| 21.102 | Battery chargers for installing in caravans and similar vehicles withstand vibrations to which they may be subjected (IEC 60335-2-29) | | N/A |
| | Vibration test as specified in IEC 60068-2-6 (IEC 60335-2-29) | | N/A |
| | Battery chargers show no damage that could impair compliance with 8.1, 15.1.1, 16.3 and cl. 29 (IEC 60335-2-29) | | N/A |
| | Connections have not worked loose (IEC 60335-2-29) | | N/A |
| 22 | CONSTRUCTION | | P |
| 22.1 | Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled | | N/A |
| 22.2 | Stationary appliance: means to ensure all-pole disconnection from the supply being provided: | | N/A |
| | - a supply cord fitted with a plug, or | | N/A |
| | - a switch complying with 24.3, or | | N/A |
| | - a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided, or | | N/A |
| | - an appliance inlet | | N/A |
| | Single-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor | | N/A |
| 22.3 | Appliance provided with pins: no undue strain on socket-outlets | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|---------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Applied torque not exceeding 0,25 Nm | | N/A |
| | Pull force of 50 N to each pin after the appliance has being placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1 mm | | N/A |
| | Each pin subjected to a torque of 0,4 Nm; the pins are not rotating, unless | | N/A |
| | rotating does not impair compliance with this standard | | N/A |
| 22.4 | Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets | | N/A |
| 22.5 | No risk of electric shock when touching the pins of the plug, for appliances having a capacitor with rated capacitance exceeding 0,1 μ F, the appliance being disconnected from the supply at the instant of voltage peak | | P |
| | Voltage not exceeding 34 V (V).....: | Measured 10.0V max. | P |
| 22.6 | Electrical insulation not affected by condensing water or leaking liquid | | N/A |
| | Electrical insulation of Class II appliances not affected if a hose ruptures or seal leaks | | N/A |
| | In case of doubt, test as described | | N/A |
| 22.7 | Adequate safeguards against the risk of excessive pressure in appliances containing liquid or gases or having steam-producing devices | | N/A |
| 22.8 | Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use | | N/A |
| 22.9 | Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances, unless | | P |
| | the substance has adequate insulating properties | | N/A |
| 22.10 | Not possible to reset voltage-maintained non-self-resetting thermal cut-outs by the operation of an automatic switching device incorporated within the appliance, if: | | N/A |
| | - a non-self-resetting thermal cut-out is required by the standard, and | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - a voltage maintained non-self-resetting thermal cut-out is used to meet it | | N/A |
| | Non-self-resetting thermal motor protectors have a trip-free action, unless | | N/A |
| | they are voltage maintained | | N/A |
| | Reset buttons of non-self-resetting controls so located or protected that accidental resetting is unlikely | | N/A |
| 22.11 | Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts | | P |
| | Obvious locked position of snap-in devices used for fixing such parts | | N/A |
| | No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing | | N/A |
| | Tests as described | | P |
| 22.12 | Handles, knobs etc. fixed in a reliable manner | | N/A |
| | Fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible | | N/A |
| | Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied | | N/A |
| | Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied | | N/A |
| 22.13 | Unlikely that handles, when gripped as in normal use, make the operator's hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only | | P |
| 22.14 | No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance | | P |
| | No exposed pointed ends of self-tapping screws or other fasteners, likely to be touched by the user in normal use or during user maintenance | | P |
| 22.15 | Storage hooks and the like for flexible cords smooth and well rounded | | N/A |
| 22.16 | Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands and no undue wear of contacts | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Cord reel tested with 6000 operations, as specified | | N/A |
| | Electric strength test of 16.3, voltage of 1000 V applied | | N/A |
| 22.17 | Spacers not removable from the outside by hand or by means of a screwdriver or a spanner | | N/A |
| 22.18 | Current-carrying parts and other metal parts resistant to corrosion | | P |
| 22.19 | Driving belts not relied upon to provide the required level of insulation, unless | | N/A |
| | constructed to prevent inappropriate replacement | | N/A |
| 22.20 | Direct contact between live parts and thermal insulation effectively prevented, unless | | P |
| | material used is non-corrosive, non-hygroscopic and non-combustible | | P |
| 22.21 | Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless | | P |
| | impregnated | | N/A |
| | This requirement does not apply to magnesium oxide and mineral ceramic fibres used for the electrical insulation of heating elements | | N/A |
| 22.22 | Appliances not containing asbestos | | P |
| 22.23 | Oils containing polychlorinated biphenyl (PCB) not used | | P |
| 22.24 | Bare heating elements, except in class III appliances or class III constructions that do not contain live parts, adequately supported | | N/A |
| | In case of rupture, the heating conductor is unlikely to come in contact with accessible metal parts | | N/A |
| 22.25 | Sagging heating conductors, except in class III appliances or class III constructions that do not contain live parts, cannot come into contact with accessible metal parts | | N/A |
| 22.26 | Output circuit supplied through a safety isolating transformer (IEC 60335-2-29) | | P |
| | No connection between the output circuit and accessible metal parts or an earthing terminal (IEC 60335-2-29) | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Insulation between parts operating at safety extra-low voltage and live parts complies with the requirements for double or reinforced insulation (IEC 60335-2-29) | | P |
| 22.27 | Parts connected by protective impedance separated by double or reinforced insulation | | P |
| 22.28 | Metal parts of Class II appliances conductively connected to gas pipes or in contact with water, separated from live parts by double or reinforced insulation | | N/A |
| 22.29 | Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation | | N/A |
| 22.30 | Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or | | P |
| | so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete | | P |
| 22.31 | Neither clearances nor creepage distances over supplementary and reinforced insulation reduced below values specified in clause 29 as a result of wear | | P |
| | Neither clearances nor creepage distances between live parts and accessible parts reduced below values for supplementary insulation if wires, screws etc. become loose | | P |
| 22.32 | Supplementary and reinforced insulation constructed or protected against pollution so that clearances or creepage distances are not reduced below the values in clause 29 | | P |
| | Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2 | | N/A |
| | Ceramic material not tightly sintered, similar materials or beads alone not used as supplementary or reinforced insulation | | N/A |
| | Insulating material in which heating conductors are embedded is considered to be basic insulation, not reinforced insulation | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Oxygen bomb test at 70 °C for 96 h and 16 h at room temperature | | N/A |
| 22.33 | Conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts are not in direct contact with live parts | | N/A |
| | Electrodes not used for heating liquids | | N/A |
| | For class II constructions, conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts, not in direct contact with basic or reinforced insulation, unless | | N/A |
| | the reinforced insulation consists of at least 3 layers | | N/A |
| | For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation, unless | | N/A |
| | the reinforced insulation consists of at least 3 layers | | N/A |
| | An air layer not used as basic or supplementary insulation in a double insulation system if likely to be bridged by leaking liquid | | N/A |
| 22.34 | Shafts of operating knobs, handles, levers etc. not live, unless | No such parts | N/A |
| | the shaft is not accessible when the part is removed | | N/A |
| 22.35 | For other than class III constructions, handles, levers and knobs, held or actuated in normal use, not becoming live in the event of a failure of basic insulation | No such parts | N/A |
| | Such parts being of metal, and their shafts or fixings are likely to become live in the event of a failure of basic insulation, are either adequately covered by insulation material or their accessible parts are separated from their shafts or fixings by supplementary insulation | | N/A |
| | This requirement does not apply to handles, levers and knobs on stationary appliances, other than those of electrical components, provided they are reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal | | N/A |
| | Insulating material covering metal handles, levers and knobs withstand the electric strength test of 16.3 for supplementary insulation | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 22.36 | For appliances other than class III, handles continuously held in the hand in normal use so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless | | N/A |
| | they are separated from live parts by double or reinforced insulation | | N/A |
| 22.37 | Capacitors in Class II appliances not connected to accessible metal parts and their casings, if of metal, separated from accessible metal parts by supplementary insulation, unless | No such construction | N/A |
| | the capacitors comply with 22.42 | | N/A |
| 22.38 | Capacitors not connected between the contacts of a thermal cut-out | No such construction | N/A |
| 22.39 | Lamp holders used only for the connection of lamps | No such parts | N/A |
| 22.40 | Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible | | N/A |
| | If the appliance cannot operate continuously, automatically or remotely without giving rise to a hazard, appliances for remote operation being fitted with a switch for stopping the operation. The actuating member of the switch being easily visible and accessible | | N/A |
| 22.41 | No components, other than lamps, containing mercury | No such parts | N/A |
| 22.42 | Protective impedance consisting of at least two separate components | | P |
| | Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited | | P |
| | Resistors checked by the test of 14.1 a) in IEC 60065 | | N/A |
| | Capacitors checked by the tests for class Y capacitors in IEC 60384-14 | | P |
| 22.43 | Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur | | N/A |
| 22.44 | Appliances not having an enclosure that is shaped or decorated like a toy | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 22.45 | When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.3 due to deformation as a result of an external force applied to the enclosure | | P |
| 22.46 | For programmable protective electronic circuits used to ensure compliance with the standard, the software contains measures to control the fault/error conditions in table R.1 | | N/A |
| | Software that contains measures to control the fault/error conditions specified in table R.2 is to be specified in parts 2 for particular constructions or to address specific hazards | | N/A |
| | These requirements are not applicable to software used for functional purpose or compliance with clause 11 | | N/A |
| 22.47 | Appliances connected to the water mains withstand the water pressure expected in normal use | | N/A |
| | No leakage from any part, including any inlet water hose | | N/A |
| 22.48 | Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water | | N/A |
| 22.49 | For remote operation, the duration of operation is to be set before the appliance can be started, unless | | N/A |
| | the appliance switches off automatically or can operate continuously without hazard | | N/A |
| 22.50 | Controls incorporated in the appliance take priority over controls actuated by remote operation | | N/A |
| 22.51 | There is a control on the appliance manually adjusted to the setting for remote operation before the appliance can be operated in this mode | | N/A |
| | There is a visual indication showing that the appliance is adjusted for remote operation | | N/A |
| | These requirements not necessary on appliances that can operate as follows, without giving rise to a hazard: | | N/A |
| | - continuously, or | | N/A |
| | - automatically, or | | N/A |
| | - remotely | | N/A |
| 22.52 | Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 22.102 | Each circuit supplied from a d.c. distribution board incorporates an overload protective device (IEC 60335-2-29) | | N/A |
| 22.103 | Battery chargers for installing in caravans or similar vehicles constructed so that they can be securely fixed to a support (IEC 60335-2-29) | | N/A |
| 23 | INTERNAL WIRING | | P |
| 23.1 | Wireways smooth and free from sharp edges | | P |
| | Wires protected against contact with burrs, cooling fins etc. | | P |
| | Wire holes in metal well-rounded or provided with bushings | | N/A |
| | Wiring effectively prevented from coming into contact with moving parts | | N/A |
| 23.2 | Beads etc. on live wires cannot change their position, and are not resting on sharp edges | | N/A |
| | Beads inside flexible metal conduits contained within an insulating sleeve | | N/A |
| 23.3 | Electrical connections and internal conductors movable relatively to each other not exposed to undue stress | | N/A |
| | Flexible metallic tubes not causing damage to insulation of conductors | | N/A |
| | Open-coil springs not used | | N/A |
| | Adequate insulating lining provided inside a coiled spring, the turns of which touch one another | | N/A |
| | No damage after 10 000 flexings for conductors flexed during normal use, or | | N/A |
| | 100 flexings for conductors flexed during user maintenance | | N/A |
| | Electric strength test of 16.3, 1000 V between live parts and accessible metal parts | | N/A |
| | Not more than 10% of the strands of any conductor broken, and | | N/A |
| | not more than 30% for wiring supplying circuits that consume no more than 15W | | N/A |
| 23.4 | Bare internal wiring sufficiently rigid and fixed | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 23.5 | The insulation of internal wiring subjected to the supply mains voltage withstanding the electrical stress likely to occur in normal use | | P |
| | Basic insulation electrically equivalent to the basic insulation of cords complying with IEC 60227 or IEC 60245, or | | N/A |
| | no breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation | | P |
| 23.6 | Sleeving used as supplementary insulation on internal wiring retained in position by clamping at both ends, or | | N/A |
| | be such that it can only be removed by breaking or cutting | | N/A |
| 23.7 | The colour combination green/yellow only used for earthing conductors | | P |
| 23.8 | Aluminium wires not used for internal wiring | | P |
| 23.9 | Stranded conductors not consolidated by soldering where they are subjected to contact pressure, unless | | N/A |
| | the contact pressure is provided by spring terminals | | P |
| 23.10 | The insulation and sheath of internal wiring, incorporated in external hoses for the connection of an appliance to the water mains, at least equivalent to that of light polyvinyl chloride sheathed flexible cord (60227 IEC 52) | | N/A |
| 24 | COMPONENTS | | P |
| 24.1 | Components comply with safety requirements in relevant IEC standards | | P |
| | List of components | (see appended table) | P |
| | If components have not been tested and found to comply with relevant IEC standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9 | | P |
| | For components mentioned in 24.1.1 to 24.1.9 no additional tests specified in the relevant component standard are necessary other than those specified in 24.1.1 to 24.1.9 | | P |

| IEC 60335-2-29 | | | |
|----------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Components not tested and found to comply with relevant IEC standard and components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance | | P |
| | Lampholders and starterholders that have not being tested and found to comply with the relevant IEC standard, tested as a part of the appliance and additionally according to the gauging and interchangeability requirements of the relevant IEC standard | | N/A |
| | No additional tests specified for nationally standardized plugs such as those detailed in IEC/TR 60083 or connectors complying with the standard sheets of IEC 60320-1 and IEC 60309 | | N/A |
| 24.1.1 | Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14 | | P |
| | If the capacitors have to be tested, they are tested according to Annex F | | N/A |
| 24.1.2 | Safety isolating transformers complying with IEC 61558-2-6 | | N/A |
| | If they have to be tested, they are tested according to Annex G | | P |
| 24.1.3 | Switches complying with IEC 61058-1, the number of cycles of operation being at least 10 000 | | N/A |
| | If they have to be tested, they are tested according to Annex H | | N/A |
| | If the switch operates a relay or contactor, the complete switching system is subjected to the test | | N/A |
| | If the switch only operates a motor starting relay complying with IEC 60730-2-10 with the number of cycles of a least 10 000 as specified, the complete switching system need not be tested | | N/A |
| 24.1.4 | Automatic controls complying with IEC 60730-1 with the relevant part 2. The number of cycles of operation being at least: | | N/A |
| | - thermostats: 10 000 | | N/A |
| | - temperature limiters: 1 000 | | N/A |
| | - self-resetting thermal cut-outs: 300 | | N/A |
| | - voltage maintained non-self-resetting thermal cut-outs: 1 000 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - other non-self-resetting thermal cut-outs: 30 | | N/A |
| | - timers: 3 000 | | N/A |
| | - energy regulators: 10 000 | | N/A |
| | The number of cycles for controls operating during clause 11 need not be declared, if the appliance meets the requirements of this standard when they are short-circuited | | N/A |
| | Thermal motor protectors are tested in combination with their motor under the conditions specified in Annex D | | N/A |
| | For water valves containing live parts and that are incorporated in external hoses for connection of an appliance to the water mains, the degree of protection declared for subclause 6.5.2 of IEC 60730-2-8 is IPX7 | | N/A |
| 24.1.5 | Appliance couplers complying with IEC 60320-1 | | P |
| | However, for appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3 | | N/A |
| | Interconnection couplers complying with IEC 60320-2-2 | | N/A |
| 24.1.6 | Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable | | N/A |
| 24.1.7 | For remote operation of the appliance via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is IEC 62151 | | N/A |
| 24.1.8 | The relevant standard for thermal links is IEC 60691 | | N/A |
| | Thermal links not complying with IEC 60691 are considered to be an intentionally weak part for the purposes of Clause 19 | | N/A |
| 24.1.9 | Contactors and relays, other than motor starting relays, tested as part of the appliance | | P |
| | They are also tested in accordance with Clause 17 of IEC 60730-1, the number of cycles of operations in 24.1.4 selected according to the contactor or relay function in the appliance | | N/A |
| 24.2 | Appliances not fitted with: | | P |
| | - switches or automatic controls in flexible cords | | P |

| IEC 60335-2-29 | | | |
|----------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - devices causing the protective device in the fixed wiring to operate in the event of a fault in the appliance | | P |
| | - thermal cut-outs that can be reset by soldering, unless | | P |
| | the solder has a melting point of at least 230 °C | | P |
| 24.3 | Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and have a contact separation in all poles, providing full disconnection under overvoltage category III conditions | | N/A |
| 24.4 | Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1 | | P |
| 24.5 | Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance, and used accordingly | | N/A |
| | Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load | | N/A |
| 24.6 | Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42 V | | N/A |
| | In addition, the motors comply with the requirements of Annex I | | N/A |
| 24.7 | Detachable hose-sets for connection of appliances to the water mains comply with IEC 61770 | | N/A |
| | They are supplied with the appliance | | N/A |
| | Appliances intended to be permanently connected to the water mains not connected by a detachable hose-set | | N/A |
| 24.8 | Motor running capacitors in appliances for which 30.2.3 is applicable and that are permanently connected in series with a motor winding, not causing a hazard in event of a failure | | N/A |
| | One or more of the following conditions are to be met: | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - the capacitors are of class P2 according to IEC 60252-1 | | N/A |
| | - the capacitors are housed within a metallic or ceramic enclosure | | N/A |
| | - the distance of separation of the outer surface to adjacent non-metallic parts exceeds 50 mm | | N/A |
| | - adjacent non-metallic parts within 50 mm withstand the needle-flame test of Annex E | | N/A |
| | - adjacent non-metallic parts within 50 mm classified as at least V-1 according to IEC 60695-11-10 | | N/A |
| 25 | SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS | | P |
| 25.1 | Appliance not intended for permanent connection to fixed wiring, means for connection to the supply: | | N/A |
| | - supply cord fitted with a plug, | | N/A |
| | - an appliance inlet having at least the same degree of protection against moisture as required for the appliance, or | | P |
| | - pins for insertion into socket-outlets | | N/A |
| 25.2 | Appliance not provided with more than one means of connection to the supply mains | | P |
| | Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown | | N/A |
| 25.3 | Appliance intended to be permanently connected to fixed wiring provided with one of the following means for connection to the supply mains: | | N/A |
| | - a set of terminals allowing the connection of a flexible cord | | N/A |
| | - a fitted supply cord | | N/A |
| | - a set of supply leads accommodated in a suitable compartment | | N/A |
| | - a set of terminals for the connection of cables of fixed wiring, cross-sectional areas specified in 26.6, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate types of cable or conduit, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support | | N/A |
| | For a fixed appliance constructed so that parts can be removed to facilitate easy installation, this requirement is met if it is possible to connect the fixed wiring without difficulty after a part of the appliance has been fixed to its support | | N/A |
| 25.4 | Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10 (mm) | | N/A |
| | Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in clause 29 | | N/A |
| 25.5 | Method for assembling the supply cord to the appliance: | | N/A |
| | - type X attachment | | N/A |
| | - type Y attachment | | N/A |
| | - type Z attachment, if allowed in relevant part 2 | | N/A |
| | Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords | | N/A |
| | For multi-phase appliances supplied with a supply cord and that are intended to be permanently connected to fixed wiring, the supply cord is assembled to the appliance by type Y attachment | | N/A |
| 25.6 | Plugs fitted with only one flexible cord | | N/A |
| 25.7 | Supply cords, other than for class III appliances, being one of the following types: | | N/A |
| | - rubber sheathed (at least 60245 IEC 53) | | N/A |
| | - polychloroprene sheathed (at least 60245 IEC 57) | | N/A |
| | - cross-linked polyvinyl chloride sheathed (at least 60245 IEC 88) | | N/A |
| | - polyvinyl chloride sheathed. Not used if they are likely to touch metal parts having a temperature rise exceeding 75 K during the test of clause 11 | | N/A |
| | <ul style="list-style-type: none"> • light polyvinyl chloride sheathed cord (60227 IEC 52), for appliances not exceeding 3 kg | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | <ul style="list-style-type: none"> ordinary polyvinyl chloride sheathed cord (60227 IEC 53), for other appliances | | N/A |
| | - heat resistant polyvinyl chloride sheathed. Not used for type X attachment other than specially prepared cords | | N/A |
| | <ul style="list-style-type: none"> heat-resistant light polyvinyl chloride sheathed cord (60227 IEC 56), for appliances not exceeding 3 kg | | N/A |
| | <ul style="list-style-type: none"> heat-resistant polyvinyl chloride sheathed cord (60227 IEC 57), for other appliances | | N/A |
| | Supply cords for class III appliances adequately insulated | | N/A |
| | Test with 500 V for 2 min for supply cords of class III appliances that contain live parts | | N/A |
| | Battery chargers for charging automobile batteries shall not be fitted with natural rubber sheathed supply cords (IEC 60335-2-29). | | N/A |
| 25.8 | Nominal cross-sectional area of supply cords not less than table 11; rated current (A); cross-sectional area (mm ²).....: | | N/A |
| 25.9 | Supply cords not in contact with sharp points or edges | | P |
| 25.10 | Supply cord of class I appliances have a green/yellow core for earthing | | P |
| 25.11 | Conductors of supply cords not consolidated by soldering where they are subject to contact pressure, unless | | P |
| | the contact pressure is provided by spring terminals | | N/A |
| 25.12 | Insulation of the supply cord not damaged when moulding the cord to part of the enclosure | | P |
| 25.13 | Inlet openings so constructed as to prevent damage to the supply cord | | P |
| | If the enclosure at the inlet opening is not of insulating material, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided | | N/A |
| | If unsheathed supply cord, a similar additional bushing or lining is required, unless the appliance is | | N/A |
| | class 0, or | | N/A |
| | a class III appliance not containing live parts | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 25.14 | Supply cords moved while in operation adequately protected against excessive flexing | | N/A |
| | Flexing test, as described: | | N/A |
| | - applied force (N).....: | | N/A |
| | - number of flexings.....: | | N/A |
| | The test does not result in: | | N/A |
| | - short-circuit between the conductors, such that the current exceeds a value of twice the rated current | | N/A |
| | - breakage of more than 10% of the strands of any conductor | | N/A |
| | - separation of the conductor from its terminal | | N/A |
| | - loosening of any cord guard | | N/A |
| | - damage to the cord or the cord guard | | N/A |
| | - broken strands piercing the insulation and becoming accessible | | N/A |
| 25.15 | For appliances with supply cord and appliances to be permanently connected to fixed wiring by a flexible cord, conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage | | N/A |
| | The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged | | N/A |
| | Pull and torque test of supply cord, values shown in table 12: mass (kg); pull (N); torque (not on automatic cord reel) (Nm) | | N/A |
| | Cord not damaged and max. 2 mm displacement of the cord | | N/A |
| 25.16 | Cord anchorages for type X attachments constructed and located so that: | | N/A |
| | - replacement of the cord is easily possible | | N/A |
| | - it is clear how the relief from strain and the prevention of twisting are obtained | | N/A |
| | - they are suitable for different types of supply cord | | N/A |
| | - cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless | | N/A |
| | they are separated from accessible metal parts by supplementary insulation | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - the cord is not clamped by a metal screw which bears directly on the cord | | N/A |
| | - at least one part of the cord anchorage securely fixed to the appliance, unless | | N/A |
| | it is part of a specially prepared cord | | N/A |
| | - screws which have to be operated when replacing the cord do not fix any other component, unless | | N/A |
| | the appliance becomes inoperative or incomplete or the parts cannot be removed without a tool | | N/A |
| | - if labyrinths can be bypassed the test of 25.15 is nevertheless withstood | | N/A |
| | - for class 0, 0I and I appliances they are of insulating material or are provided with an insulating lining, unless | | N/A |
| | failure of the insulation of the cord does not make accessible metal parts live | | N/A |
| | - for class II appliances they are of insulating material, or | | N/A |
| | if of metal, they are insulated from accessible metal parts by supplementary insulation | | N/A |
| | After the test of 25.15, under the conditions specified, the conductors have not moved by more than 1 mm in the terminals | | N/A |
| 25.17 | Adequate cord anchorages for type Y and Z attachment, test with the cord supplied with the appliance | | N/A |
| 25.18 | Cord anchorages only accessible with the aid of a tool, or | | N/A |
| | Constructed so that the cord can only be fitted with the aid of a tool | | N/A |
| 25.19 | Type X attachment, glands not used as cord anchorage in portable appliances | | N/A |
| | Tying the cord into a knot or tying the cord with string not used | | N/A |
| 25.20 | The insulated conductors of the supply cord for type Y and Z attachment additionally insulated from accessible metal parts | | N/A |
| 25.21 | Space for supply cord for type X attachment or for connection of fixed wiring constructed: | | N/A |

| IEC 60335-2-29 | | | |
|----------------|---|---------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - to permit checking of conductors with respect to correct positioning and connection before fitting any cover | | N/A |
| | - so there is no risk of damage to the conductors or their insulation when fitting the cover | | N/A |
| | - for portable appliances, so that the uninsulated end of a conductor, if it becomes free from the terminal, prevented from contact with accessible metal parts | | N/A |
| | 2 N test to the conductor for portable appliances; no contact with accessible metal parts | | N/A |
| 25.22 | Appliance inlets: | | P |
| | - live parts not accessible during insertion or removal | | P |
| | Requirement not applicable to appliance inlets complying with IEC 60320-1 | | P |
| | - connector can be inserted without difficulty | | P |
| | - the appliance is not supported by the connector | | P |
| | - not for cold conditions if temp. rise of external metal parts exceeds 75 K during clause 11, unless | No such metal parts | N/A |
| | the supply cord is unlikely to touch such metal parts | | N/A |
| 25.23 | Interconnection cords comply with the requirements for the supply cord, except that: | | N/A |
| | - the cross-sectional area of the conductors is determined on the basis of the maximum current during clause 11 | | N/A |
| | - the thickness of the insulation may be reduced | | N/A |
| | If necessary, electric strength test of 16.3 | | N/A |
| 25.24 | Interconnection cords not detachable without the aid of a tool if compliance with this standard is impaired when they are disconnected | | N/A |
| 25.25 | Dimensions of pins that are inserted into socket-outlets compatible with the dimensions of the relevant socket-outlet. | | N/A |
| | Dimensions of pins and engagement face in accordance with the dimensions of the relevant plug in IEC/TR 60083 | | N/A |
| 26 | TERMINALS FOR EXTERNAL CONDUCTORS | | P |

| IEC 60335-2-29 | | | |
|----------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 26.1 | Appliances provided with terminals or equally effective devices for connection of external conductors | | P |
| | Terminals only accessible after removal of a non-detachable cover, except | | P |
| | for class III appliances that do not contain live parts | | N/A |
| | Earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection | | N/A |
| 26.2 | Appliances with type X attachment and appliances for the connection of cables to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless | | N/A |
| | the connections are soldered | | N/A |
| | Screws and nuts not used to fix any other component, except | | N/A |
| | internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors | | N/A |
| | If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone, unless | | N/A |
| | barriers provided so that neither clearances nor creepage distances between live parts and other metal parts reduced below the values for supplementary insulation if the conductor becomes free at the soldered joint | | N/A |
| 26.3 | Terminals for type X attachment and for connection of cables of fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure but without damaging the conductor | | N/A |
| | Terminals fixed so that when the clamping means is tightened or loosened: | | N/A |
| | - the terminal does not become loose | | N/A |
| | - internal wiring is not subjected to stress | | N/A |
| | - neither clearances nor creepage distances are reduced below the values in clause 29 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Compliance checked by inspection and by the test of subclause 9.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified (Nm) | | N/A |
| | No deep or sharp indentations of the conductors | | N/A |
| 26.4 | Terminals for type X attachment, except those having a specially prepared cord and those for the connection of cables of fixed wiring, no special preparation of conductors such as by soldering, use of cable lugs, eyelets or similar, and | | N/A |
| | so constructed or placed that conductors prevented from slipping out when clamping screws or nuts are tightened | | N/A |
| 26.5 | Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard | | N/A |
| | Stranded conductor test, 8 mm insulation removed | | N/A |
| | No contact between live parts and accessible metal parts and, | | N/A |
| | for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only | | N/A |
| | This requirement does not apply to the terminals of the output circuit (IEC 60335-2-29). | | N/A |
| 26.6 | Terminals for type X attachment and for connection of cables of fixed wiring suitable for connection of conductors with cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm ²)..... | | N/A |
| | If a specially prepared cord is used, terminals need only be suitable for that cord | | N/A |
| 26.7 | Terminals for type X attachment, except in class III appliances not containing live parts, accessible after removal of a cover or part of the enclosure | | N/A |
| 26.8 | Terminals for the connection of fixed wiring, including the earthing terminal, located close to each other | | N/A |
| 26.9 | Terminals of the pillar type constructed and located as specified | | N/A |
| 26.10 | Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | conductors ends fitted with means suitable for screw terminals | | N/A |
| | Pull test of 5 N to the connection | | N/A |
| 26.11 | For type Y and Z attachment, soldered, welded, crimped or similar connections may be used | | N/A |
| | For Class II appliances, the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone | | N/A |
| | If soldering, welding or crimping alone used, barriers provided so that clearances and creepage distances between live parts and other metal parts are not reduced below the values for supplementary insulation if the conductor becomes free | | N/A |
| 27 | PROVISION FOR EARTHING | | P |
| 27.1 | Accessible metal parts of Class 0I and I appliances permanently and reliably connected to an earthing terminal or earthing contact of the appliance inlet | | P |
| | Earthing terminals and earthing contacts not connected to the neutral terminal | | P |
| | Class 0, II and III appliances have no provision for earthing | | N/A |
| | Safety extra-low voltage circuits not earthed, unless | | N/A |
| | protective extra-low voltage circuits | | N/A |
| 27.2 | Clamping means of earthing terminals adequately secured against accidental loosening | | P |
| | Terminals for the connection of external equipotential bonding conductors allow connection of conductors of 2,5 to 6 mm ² , and | | N/A |
| | do not provide earthing continuity between different parts of the appliance, and | | N/A |
| | conductors cannot be loosened without the aid of a tool | | P |
| 27.3 | For a detachable part having an earth connection and being plugged into another part of the appliance, the earth connection is made before and separated after current-carrying connections when removing the part | | N/A |
| | For appliances with supply cords, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 27.4 | No risk of corrosion resulting from contact between parts of the earthing terminal and the copper of the earthing conductor or other metal | | P |
| | Parts providing earthing continuity, other than parts of a metal frame or enclosure, have adequate resistance to corrosion | | P |
| | If of steel, these parts provided with an electroplated coating with a thickness at least 5 µm | | N/A |
| | Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure | | N/A |
| | In the body of the earthing terminal is a part of a frame or enclosure of aluminium or aluminium alloys, precautions taken to avoid risk of corrosion | | N/A |
| 27.5 | Low resistance of connection between earthing terminal and earthed metal parts | | P |
| | This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided the clearances of basic insulation are based on the rated voltage of the appliance | | N/A |
| | Resistance not exceeding 0,1 Ω at the specified low-resistance test (Ω).....: | 0.005Ω | P |
| 27.6 | The printed conductors of printed circuit boards not used to provide earthing continuity in hand-held appliances. | | N/A |
| | They may be used to provide earthing continuity in other appliances if at least two tracks are used with independent soldering points and the appliance complies with 27.5 for each circuit | | N/A |
| 28 | SCREWS AND CONNECTIONS | | P |
| 28.1 | Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses | | P |
| | Screws not of soft metal liable to creep, such as zinc or aluminium | | N/A |
| | Diameter of screws of insulating material min. 3 mm | | P |
| | Screws of insulating material not used for any electrical connections or connections providing earthing continuity | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Screws used for electrical connections or connections providing earthing continuity screwed into metal | | N/A |
| | Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation | | P |
| | For type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw impairs basic insulation | | N/A |
| | For screws and nuts; torque-test as specified in table 14.....: | | P |
| 28.2 | Electrical connections and connections providing earthing continuity constructed so that contact pressure is not transmitted through non-ceramic insulating material liable to shrink or distort, unless | | N/A |
| | there is resiliency in the metallic parts to compensate for shrinkage or distortion of the insulating material | | N/A |
| | This requirement does not apply to electrical connections in circuits of appliances for which: | | N/A |
| | <ul style="list-style-type: none"> • 30.2.2 is applicable and that carry a current not exceeding 0,5 A | | N/A |
| | <ul style="list-style-type: none"> • 30.2.3 is applicable and that carry a current not exceeding 0,2 A | | N/A |
| 28.3 | Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together | | N/A |
| | Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread | | N/A |
| | Thread-cutting (self-tapping) screws not used if they are likely to be operated by the user or installer | | N/A |
| | Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection: | | N/A |
| | - in normal use, | | N/A |
| | - during user maintenance, | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|----------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - when replacing a supply cord having a type X attachment, or | | N/A |
| | - during installation | | N/A |
| | At least two screws being used for each connection providing earthing continuity, unless | | N/A |
| | the screw forms a thread having a length of at least half the diameter of the screw | | N/A |
| 28.4 | Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity | | N/A |
| | This requirement does not apply to screws in the earthing circuit if at least two screws are used, or | | N/A |
| | if an alternative earthing circuit is provided | | N/A |
| | Rivets for electrical connections or connections providing earthing continuity secured against loosening if the connections are subjected to torsion | | N/A |
| 29 | CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION | | P |
| | Clearances, creepage distances and solid insulation withstand electrical stress | | P |
| | For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), Annex J applies | | N/A |
| | The microenvironment is pollution degree 1 under type 1 protection | | N/A |
| | For type 2 protection, the spacing between the conductors before the protection is applied is not less than the values specified in Table 1 of IEC 60664-3 | | N/A |
| | These values apply to functional, basic, supplementary and reinforced insulation.....: | | N/A |
| 29.1 | Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless | (see appended table) | P |
| | for basic insulation and functional insulation they comply with the impulse voltage test of clause 14 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | However, if the distances are affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable | | P |
| | Impulse voltage test is not applicable: | | P |
| | - when the microenvironment is pollution degree 3, or | | N/A |
| | - for basic insulation of class 0 and class 01 appliances | | N/A |
| | Appliances are in overvoltage category II | | P |
| | A force of 2 N is applied to bare conductors, other than heating elements | | N/A |
| | A force of 30 N is applied to accessible surfaces | | P |
| 29.1.1 | Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage | | P |
| | The values of table 16 or the impulse voltage test of clause 14 are applicable.....: | (see appended table) | P |
| | Clearance at the terminals of tubular sheathed heating elements may be reduced to 1,0 mm if the microenvironment is pollution degree 1 | | N/A |
| | Lacquered conductors of windings considered to be bare conductors | | P |
| 29.1.2 | Clearances of supplementary insulation not less than those specified for basic insulation in table 16: | (see appended table) | P |
| 29.1.3 | Clearances of reinforced insulation not less than those specified for basic insulation in table 16, using the next higher step for rated impulse voltage | (see appended table) | P |
| | For double insulation, with no intermediate conductive part between basic and supplementary insulation, clearances are measured between live parts and the accessible surface, and the insulation system is treated as reinforced insulation | | P |
| 29.1.4 | Clearances for functional insulation are the largest values determined from: | | P |
| | - table 16 based on the rated impulse voltage | (see appended table) | P |
| | - table F.7a in IEC 60664-1, frequency not exceeding 30 kHz | | N/A |
| | - clause 4 of IEC 60664-4, frequency exceeding 30 kHz | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--|----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | If values of table 16 are largest, the impulse voltage test of clause 14 may be applied instead, unless | | P |
| | the microenvironment is pollution degree 3, or | | N/A |
| | the distances can be affected by wear, distortion, movement of the parts or during assembly | | N/A |
| | However, clearances are not specified if the appliance complies with clause 19 with the functional insulation short-circuited | | N/A |
| | Lacquered conductors of windings considered to be bare conductors | | P |
| | However, clearances at crossover points are not measured | | P |
| | Clearance between surfaces of PTC heating elements may be reduced to 1mm | | N/A |
| 29.1.5 | Appliances having higher working voltages than rated voltage, clearances for basic insulation are the largest values determined from: | | P |
| | - table 16 based on the rated impulse voltage | (see appended table) | P |
| | - table F.7a in IEC 60664-1, frequency not exceeding 30 kHz | | N/A |
| | - clause 4 of IEC 60664-4, frequency exceeding 30 kHz | | N/A |
| | If clearances for basic insulation are selected from Table F.7a of IEC 60664-1 or Clause 4 of IEC 60664-4, the clearances of supplementary insulation are not less than those specified for basic insulation | | N/A |
| | If clearances for basic insulation are selected from Table F.7a of IEC 60664-1, the clearances of reinforced insulation dimensioned as specified in Table F.7a are to withstand 160% of the withstand voltage required for basic insulation | | N/A |
| | If clearances for basic insulation are selected from Clause 4 of IEC 60664-4, the clearances of reinforced insulation are twice the value required for basic insulation | | N/A |
| | If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation are based on the working voltage used as the rated voltage in table 15 | | P |
| 29.2 | Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree | (see appended table) | P |
| | Pollution degree 2 applies, unless | | P |
| | - precautions taken to protect the insulation; pollution degree 1 | | N/A |
| | - insulation subjected to conductive pollution; pollution degree 3 | | N/A |
| | A force of 2 N is applied to bare conductors, other than heating elements | | N/A |
| | A force of 30 N is applied to accessible surfaces | | P |
| | In a double insulation system, the working voltage for both the basic and supplementary insulation is taken as the working voltage across the complete double insulation system | | P |
| 29.2.1 | Creepage distances of basic insulation not less than specified in table 17 | (see appended table) | P |
| | However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 17 | | N/A |
| | Except for pollution degree 1, corresponding creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14 | | N/A |
| 29.2.2 | Creepage distances of supplementary insulation at least those specified for basic insulation in table 17, or | (see appended table) | P |
| | Table 2 of IEC 60664-4, as applicable | | N/A |
| 29.2.3 | Creepage distances of reinforced insulation at least double those specified for basic insulation in table 17, or | (see appended table) | P |
| | Table 2 of IEC 60664-4, as applicable | | N/A |
| 29.2.4 | Creepage distances of functional insulation not less than specified in table 18 | (see appended table) | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 18.....: | | N/A |
| | Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited | | P |
| 29.3 | Supplementary and reinforced insulation have adequate thickness, or a sufficient number of layers, to withstand the electrical stresses | | P |
| | Compliance checked: | | P |
| | - by measurement, in accordance with 29.3.1, or | | P |
| | - by an electric strength test in accordance with 29.3.2, or | | P |
| | - by an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and | | N/A |
| | for accessible parts of reinforced insulation consisting of a single layer, by measurement in accordance with 29.3.4, or | | N/A |
| | - as specified in subclause 6.3 of IEC 60664-4 for insulation that is subjected to any periodic voltage having a frequency exceeding 30 kHz | | N/A |
| 29.3.1 | Supplementary insulation have a thickness of at least 1 mm | | P |
| | Reinforced insulation have a thickness of at least 2 mm | | P |
| 29.3.2 | Each layer of material withstand the electric strength test of 16.3 for supplementary insulation | | P |
| | Supplementary insulation consist of at least 2 layers | | P |
| | Reinforced insulation consist of at least 3 layers | | P |
| 29.3.3 | The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by | | N/A |
| | the electric strength test of 16.3 | | N/A |
| | If the temperature rise during the tests of clause 19 does not exceed the value specified in table 3, the test of IEC 60068-2-2 is not carried out | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|----------------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 29.3.4 | Thickness of accessible parts of reinforced insulation consisting of a single layer not less than specified in table 19.....: | | N/A |
| 30 | RESISTANCE TO HEAT AND FIRE | | P |
| 30.1 | External parts of non-metallic material, | | P |
| | parts supporting live parts, and | | P |
| | parts of thermoplastic material providing supplementary or reinforced insulation | | P |
| | sufficiently resistant to heat | | P |
| | Ball-pressure test according to IEC 60695-10-2 | | P |
| | External parts tested at 40 °C plus the maximum temperature rise determined during the test of clause 11, or at 75 °C, whichever is the higher; temperature (°C).....: | (see appended table) | P |
| | Parts supporting live parts tested at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125 °C, whichever is the higher; temperature (°C).....: | (see appended table) | P |
| | Parts of thermoplastic material providing supplementary or reinforced insulation tested at 25 °C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C) | (see appended table) | P |
| 30.2 | Parts of non-metallic material resistant to ignition and spread of fire | | P |
| | This requirement does not apply to: | | N/A |
| | parts having a mass not exceeding 0,5 g, provided the cumulative effect is unlikely to propagate flames that originate inside the appliance by propagating flames from one part to another, or | | N/A |
| | decorative trims, knobs and other parts unlikely to be ignited or to propagate flames that originate inside the appliance | | N/A |
| | Compliance checked by the test of 30.2.1, and in addition: | | P |
| | - for attended appliances, 30.2.2 applies | | N/A |
| | - for unattended appliances, 30.2.3 applies | | P |
| | For appliances for remote operation, 30.2.3 applies | | N/A |
| | For base material of printed circuit boards, 30.2.4 applies | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 30.2.1 | Parts of non-metallic material subjected to the glow-wire test of IEC 60695-2-11 at 550 °C | | P |
| | However, test not carried out if the material is classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 550 °C, or | | N/A |
| | the material is classified at least HB40 according to IEC 60695-11-10 | | N/A |
| | Parts for which the glow-wire test cannot be carried out need to meet the requirements in ISO 9772 for material classified HBF | | N/A |
| 30.2.2 | Appliances operated while attended, parts of non-metallic material supporting current-carrying connections, and | | N/A |
| | parts of non-metallic material within a distance of 3mm of such connections, | | N/A |
| | subjected to the glow-wire test of IEC 60695-2-11 | | N/A |
| | The test severity is: | | N/A |
| | - 750 °C, for connections carrying a current exceeding 0,5 A during normal operation | | N/A |
| | - 650 °C, for other connections | | N/A |
| | Glow-wire applied to an interposed shielding material, if relevant | | N/A |
| | The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least: | | N/A |
| | - 750 °C, for connections carrying a current exceeding 0,5 A during normal operation | | N/A |
| | - 650 °C, for other connections | | N/A |
| | The glow-wire test is also not carried out on small parts. These parts are to: | | N/A |
| | - comprise material having a glow-wire flammability index of at least 750 °C, or 650 °C as appropriate, or | | N/A |
| | - comply with the needle-flame test of Annex E, or | | N/A |
| | - comprise material classified as V-0 or V-1 according to IEC 60695-11-10 | | N/A |
| | Glow-wire test not applicable to conditions as specified | | N/A |
| 30.2.3 | Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2 | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The tests are not applicable to conditions as specified | | N/A |
| 30.2.3.1 | Parts of non-metallic material supporting connections carrying a current exceeding 0,2 A during normal operation, and | | P |
| | parts of non-metallic material, other than small parts, within a distance of 3 mm, | | P |
| | subjected to the glow-wire test of IEC 60695-2-11 with a test severity of 850 °C | | P |
| | Glow-wire applied to an interposed shielding material, if relevant | | N/A |
| | The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 850 °C | | N/A |
| 30.2.3.2 | Parts of non-metallic material supporting connections, and | | P |
| | parts of non-metallic material within a distance of 3mm, | | P |
| | subjected to glow-wire test of IEC 60695-2-11 | | P |
| | The test severity is: | | P |
| | - 750 °C, for connections carrying a current exceeding 0,2 A during normal operation | | P |
| | - 650 °C, for other connections | | P |
| | Glow-wire applied to an interposed shielding material, if relevant | | N/A |
| | However, the glow-wire test of 750 °C or 650 °C as appropriate, is not carried out on parts of material fulfilling both or either of the following classifications: | | N/A |
| | - a glow-wire ignition temperature according to IEC 60695-2-13 of at least: | | N/A |
| | <ul style="list-style-type: none"> • 775 °C, for connections carrying a current exceeding 0,2 A during normal operation | | N/A |
| | <ul style="list-style-type: none"> • 675 °C, for other connections | | N/A |
| | - a glow-wire flammability index according to IEC 60695-2-12 of at least: | | N/A |
| | - 750 °C, for connections carrying a current exceeding 0,2 A during normal operation | | N/A |
| | - 650 °C, for other connections | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The glow-wire test is also not carried out on small parts. These parts are to: | | N/A |
| | - comprise material having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or | | N/A |
| | - comprise material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or | | N/A |
| | - comply with the needle-flame test of Annex E, or | | N/A |
| | - comprise material classified as V-0 or V-1 according to IEC 60695-11-10 | | N/A |
| | The consequential needle-flame test of Annex E applied to non-metallic parts that encroach within the vertical cylinder placed above the centre of the connection zone and on top of the non-metallic parts supporting current-carrying connections, and parts of non-metallic material within a distance of 3 mm of such connections if these parts are those: | | N/A |
| | - parts that withstood the glow-wire test of IEC 60695-2-11 of 750 °C or 650 °C as appropriate, but produce a flame that persist longer than 2 s, or | | N/A |
| | - parts that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or | | N/A |
| | - small parts, that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or | | N/A |
| | - small parts for which the needle-flame test of Annex E was applied, or | | N/A |
| | - small parts for which a material classification of V-0 or V-1 was applied | | N/A |
| | However, the consequential needle-flame test is not carried out on non-metallic parts, including small parts, within the cylinder that are: | | N/A |
| | - parts having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or | | N/A |
| | - parts comprising material classified as V-0 or V-1 according to IEC 60695-11-10, or | | N/A |
| | - parts shielded by a flame barrier that meets the needle-flame test of Annex E or that comprises material classified as V-0 or V-1 according to IEC 60695-11-10 | | N/A |
| 30.2.4 | Base material of printed circuit boards subjected to the needle-flame test of Annex E | | P |
| | Test not applicable to conditions as specified | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 31 | RESISTANCE TO RUSTING | | P |
| | Relevant ferrous parts adequately protected against rusting | | P |
| | Tests specified in part 2 when necessary | | N/A |
| 32 | RADIATION, TOXICITY AND SIMILAR HAZARDS | | P |
| | Appliance does not emit harmful radiation or present a toxic or similar hazard due to their operation in normal use | | P |
| | Compliance is checked by the limits or tests specified in part 2, if relevant | | N/A |
| A | ANNEX A (INFORMATIVE) ROUTINE TESTS | | N/A |
| | Description of routine tests to be carried out by the manufacturer | | N/A |
| A.2 | Electric strength test | | N/A |
| | An electric strength test is carried out between the input and output circuits, the test voltage being: | | N/A |
| | - 2 000 V, for battery chargers having a rated voltage not exceeding 150 V; | | N/A |
| | - 2 500 V, for other battery chargers. | | N/A |
| B | ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES | | N/A |
| | The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance | | N/A |
| | This annex does not apply to battery chargers | | N/A |
| 3.1.9 | Appliance operated under the following conditions: | | N/A |
| | - the appliance, supplied by its fully charged battery, operated as specified in relevant part 2 | | N/A |
| | - the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate | | N/A |
| | -if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in relevant part 2 | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - if the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed | | N/A |
| 3.6.2 | Part to be removed in order to discard the battery is not considered to be detachable | | N/A |
| 5.B.101 | Appliances supplied from the supply mains tested as specified for motor-operated appliances | | N/A |
| 7.1 | Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals | | N/A |
| | The positive terminal indicated by symbol IEC 60417-5005 and the negative terminal by symbol IEC 60417-5006 | | N/A |
| 7.6 | Symbols 60417-5005 and IEC 60417-5006 | | N/A |
| 7.12 | The instructions give information regarding charging | | N/A |
| | The instructions for appliances incorporating batteries intended to be replaced by the user includes required information | | N/A |
| | Details about how to remove batteries containing materials hazardous to the environment given | | N/A |
| 7.15 | Markings placed on the part of the appliance connected to the supply mains | | N/A |
| 8.2 | Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment | | N/A |
| | If the appliance can be operated without batteries, double or reinforced insulation required | | N/A |
| 11.7 | The battery is charged for the period stated in the instructions or 24 h | | N/A |
| 19.1 | Appliances subjected to tests of 19.B.101, 19.B.102 and 19.B.103 | | N/A |
| 19.10 | Not applicable | | N/A |
| 19.B.101 | Appliances supplied at rated voltage for 168 h, the battery being continually charged | | N/A |
| 19.B.102 | For appliances having batteries that can be removed without the aid of a tool, short-circuit of the terminals of the battery, the battery being fully charged, | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 19.B.103 | Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction | | N/A |
| 21.B.101 | Appliances having pins for insertion into socket-outlets have adequate mechanical strength | | N/A |
| | Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-31, the number of falls being: | | N/A |
| | - 100, if the mass of the part does not exceed 250 g (g) | | N/A |
| | - 50, if the mass of the part exceeds 250 g | | N/A |
| | After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met | | N/A |
| 22.3 | Appliances having pins for insertion into socket-outlets tested as fully assembled as possible | | N/A |
| 25.13 | An additional lining or bushing not required for interconnection cords in class III appliances or class III constructions operating at safety extra-low voltage not containing live parts | | N/A |
| 30.2 | For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies | | N/A |
| | For other parts, 30.2.2 applies | | N/A |
| C | ANNEX C (NORMATIVE) AGEING TEST ON MOTORS | | N/A |
| | Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding | | N/A |
| | Test conditions as specified | | N/A |
| D | ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS | | N/A |
| | Applicable to appliances having motors that incorporate thermal motor protectors necessary for compliance with the standard | | N/A |
| | Test conditions as specified | | N/A |
| E | ANNEX E (NORMATIVE) NEEDLE-FLAME TEST | | P |
| | Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications: | | P |
| 7 | Severities | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The duration of application of the test flame is 30 s ± 1 s | | P |
| 9 | Test procedure | | P |
| 9.1 | The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of Figure 1 | | P |
| 9.2 | The first paragraph does not apply | | P |
| | If possible, the flame is applied at least 10 mm from a corner | | P |
| 9.3 | The test is carried out on one specimen | | P |
| | If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test | | N/A |
| 11 | Evaluation of test results | | P |
| | The duration of burning not exceeding 30 s | | N/A |
| | However, for printed circuit boards, the duration of burning not exceeding 15 s | | P |
| F | ANNEX F (NORMATIVE) CAPACITORS | | N/A |
| | Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications: | | N/A |
| 1.5 | Terms and definitions | | N/A |
| 1.5.3 | Class X capacitors tested according to subclass X2 | | N/A |
| 1.5.4 | This subclause is applicable | | N/A |
| 1.6 | Marking | | N/A |
| | Items a) and b) are applicable | | N/A |
| 3.4 | Approval testing | | N/A |
| 3.4.3.2 | Table 3 is applicable as described | | N/A |
| 4.1 | Visual examination and check of dimensions | | N/A |
| | This subclause is applicable | | N/A |
| 4.2 | Electrical tests | | N/A |
| 4.2.1 | This subclause is applicable | | N/A |
| 4.2.5 | This subclause is applicable | | N/A |
| 4.2.5.2 | Only table 11 is applicable | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Values for test A apply | | N/A |
| | However, for capacitors in heating appliances the values for test B or C apply | | N/A |
| 4.12 | Damp heat, steady state | | N/A |
| | This subclause is applicable | | N/A |
| | Only insulation resistance and voltage proof are checked | | N/A |
| 4.13 | Impulse voltage | | N/A |
| | This subclause is applicable | | N/A |
| 4.14 | Endurance | | N/A |
| | Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 are applicable | | N/A |
| 4.14.7 | Only insulation resistance and voltage proof are checked | | N/A |
| | No visible damage | | N/A |
| 4.17 | Passive flammability test | | N/A |
| | This subclause is applicable | | N/A |
| 4.18 | Active flammability test | | N/A |
| | This subclause is applicable | | N/A |
| G | ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS | | P |
| | The following modifications to this standard are applicable for safety isolating transformers: | | P |
| 7 | Marking and instructions | | P |
| 7.1 | Transformers for specific use marked with: | | N/A |
| | -name, trademark or identification mark of the manufacturer or responsible vendor.....: | | N/A |
| | -model or type reference | | N/A |
| 17 | Overload protection of transformers and associated circuits | | P |
| | Fail-safe transformers comply with subclause 15.5 of IEC 61558-1 | | N/A |
| 22 | Construction | | P |
| | Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable | | P |
| 29 | Clearances, creepage distances and solid insulation | | P |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 29.1, 29.2, 29.3 | The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply | | P |
| | For insulated winding wires complying with subclause 19.12.3 of IEC 61558-1 there are no requirements for clearances or creepage distances | | P |
| | For windings providing reinforced insulation, the distance specified in item 2c of table 13 of IEC 61558-1 is not assessed | | P |
| | For safety isolating transformers subjected to periodic voltages with a frequency exceeding 30 kHz, the clearances, creepage distances and solid insulation values specified in IEC 60664-4 are applicable, if greater than the values specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 | | N/A |
| H | ANNEX H (NORMATIVE) SWITCHES | | N/A |
| | Switches comply with the following clauses of IEC 61058-1, as modified below: | | N/A |
| | The tests of IEC 61058-1 carried out under the conditions occurring in the appliance | | N/A |
| | Before being tested, switches are operated 20 times without load | | N/A |
| 8 | Marking and documentation | | N/A |
| | Switches are not required to be marked | | N/A |
| | However, a switch that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference | | N/A |
| 13 | Mechanism | | N/A |
| | The tests may be carried out on a separate sample | | N/A |
| 15 | Insulation resistance and dielectric strength | | N/A |
| 15.1 | Not applicable | | N/A |
| 15.2 | Not applicable | | N/A |
| 15.3 | Applicable for full disconnection and micro-disconnection | | N/A |
| 17 | Endurance | | N/A |
| | Compliance is checked on three separate appliances or switches | | N/A |
| | For 17.2.4.4, the number of cycles declared according to 7.1.4 is 10 000, unless | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | otherwise specified in 24.1.3 of the relevant part 2 of IEC 60335.....: | | N/A |
| | Switches for operation under no load and which can be operated only by a tool, and | | N/A |
| | switches operated by hand that are interlocked so that they cannot be operated under load, | | N/A |
| | are not subjected to the tests | | N/A |
| | However, switches without this interlock are subjected to the test of 17.2.4.4 for 100 cycles of operation | | N/A |
| | Subclauses 17.2.2 and 17.2.5.2 not applicable | | N/A |
| | The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in IEC 60335-1 | | N/A |
| | The temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of IEC 60335-1 (K) | | N/A |
| 20 | Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies | | N/A |
| | This clause is applicable to clearances and creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24 | | N/A |
| I | ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE | | N/A |
| | The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance: | | N/A |
| 8 | Protection against access to live parts | | N/A |
| 8.1 | Metal parts of the motor are considered to be bare live parts | | N/A |
| 11 | Heating | | N/A |
| 11.3 | The temperature rise of the body of the motor is determined instead of the temperature rise of the windings | | N/A |
| 11.8 | The temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material | | N/A |
| 16 | Leakage current and electric strength | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 16.3 | Insulation between live parts of the motor and its other metal parts is not subjected to the test | | N/A |
| 19 | Abnormal operation | | N/A |
| 19.1 | The tests of 19.7 to 19.9 are not carried out | | N/A |
| 19.1.101 | Appliance operated at rated voltage with each of the following fault conditions: | | — |
| | - short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit | | N/A |
| | - short circuit of each diode of the rectifier | | N/A |
| | - open circuit of the supply to the motor | | N/A |
| | - open circuit of any parallel resistor, the motor being in operation | | N/A |
| | Only one fault simulated at a time, the tests carried out consecutively | | N/A |
| 22 | Construction | | N/A |
| 22.1.101 | For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation | | N/A |
| | Compliance checked by the tests specified for double and reinforced insulation | | N/A |
| J | ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS | | N/A |
| | Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications: | | N/A |
| 5.7 | Conditioning of the test specimens | | N/A |
| | When production samples are used, three samples of the printed circuit board are tested | | N/A |
| 5.7.1 | Cold | | N/A |
| | The test is carried out at -25 °C | | N/A |
| 5.7.3 | Rapid change of temperature | | N/A |
| | Severity 1 is specified | | N/A |
| 5.9 | Additional tests | | N/A |
| | This subclause is not applicable | | N/A |
| K | ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES | | P |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The information on overvoltage categories is extracted from IEC 60664-1 | | P |
| | Overvoltage category is a numeral defining a transient overvoltage condition | | P |
| | Equipment of overvoltage category IV is for use at the origin of the installation | | N/A |
| | Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements | | N/A |
| | Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation | | P |
| | If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies | | N/A |
| | Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level | | N/A |
| L | ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES | | P |
| | Information for the determination of clearances and creepage distances | | P |
| M | ANNEX M (NORMATIVE) POLLUTION DEGREE | | P |
| | The information on pollution degrees is extracted from IEC 60664-1 | | P |
| | Pollution | | p |
| | The microenvironment determines the effect of pollution on the insulation, taking into account the macroenvironment | | P |
| | Means may be provided to reduce pollution at the insulation by effective enclosures or similar | | P |
| | Minimum clearances specified where pollution may be present in the microenvironment | | P |
| | Degrees of pollution in the microenvironment | | P |
| | For evaluating creepage distances, the following degrees of pollution in the microenvironment are established: | | P |

| IEC 60335-2-29 | | | |
|----------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence | | N/A |
| | - pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected | | P |
| | - pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected | | N/A |
| | - pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow | | N/A |
| N | ANNEX N (NORMATIVE) PROOF TRACKING TEST | | P |
| | The proof tracking test is carried out in accordance with IEC 60112 with the following modifications: | | P |
| 7 | Test apparatus | | P |
| 7.3 | Test solutions | | P |
| | Test solution A is used | | P |
| 10 | Determination of proof tracking index (PTI) | | P |
| 10.1 | Procedure | | P |
| | The proof voltage is 100V, 175V, 400V or 600V ...: | 175 | P |
| | The test is carried out on five specimens | | P |
| | In case of doubt, additional test with proof voltage reduced by 25 V, the number of drops increased to 100 | | N/A |
| 10.2 | Report | | P |
| | The report states if the PTI value was based on a test using 100 drops with a test voltage of (PTI-25) V | | N/A |
| O | ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30 | | P |
| | Description of tests for determination of resistance to heat and fire | | P |
| P | ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Modifications applicable for class 0 and 01 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE | | N/A |
| | Modifications may also be applied to class 1 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WdaE, if liable to be connected to a supply mains that excludes the protective earthing conductor | | N/A |
| 5.7 | The ambient temperature for the tests of clauses 11 and 13 is 40 +3/0 °C | | N/A |
| 7.1 | The appliance marked with the letters WDaE | | N/A |
| 7.12 | The instructions state that the appliance is to be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30 mA | | N/A |
| | The instructions state that the appliance is considered to be suitable for use in countries having a warm damp equable climate, but may also be used in other countries | | N/A |
| 11.8 | The values of Table 3 are reduced by 15 K | | N/A |
| 13.2 | The leakage current for class I appliances not exceeding 0,5 mA | | N/A |
| 15.3 | The value of t is 37 °C | | N/A |
| 16.2 | The leakage current for class I appliances not exceeding 0,5 mA (mA): | | N/A |
| 19.13 | The leakage current test of 16.2 is applied in addition to the electric strength test of 16.3 | | N/A |
| Q | ANNEX Q (INFORMATIVE) SEQUENCE OF TESTS FOR THE EVALUATION OF ELECTRONIC CIRCUITS | | P |
| | Description of tests for appliances incorporating electronic circuits | | P |
| R | ANNEX R (NORMATIVE) SOFTWARE EVALUATION | | N/A |
| | Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 validated in accordance with the requirements of this annex | | N/A |
| R.1 | Programmable electronic circuits using software | | N/A |
| | Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 constructed so that the software does not impair compliance with the requirements of this standard | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| R.2 | Requirements for the architecture | | N/A |
| | Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 use measures to control and avoid software-related faults/errors in safety-related data and safety-related segments of the software | | N/A |
| R.2.1.1 | Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.2 have one of the following structures: | | N/A |
| | - single channel with periodic self-test and monitoring | | N/A |
| | - dual channel (homogenous) with comparison | | N/A |
| | - dual channel (diverse) with comparison | | N/A |
| | Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 have one of the following structures: | | N/A |
| | - single channel with functional test | | N/A |
| | - single channel with periodic self-test | | N/A |
| | - dual channel without comparison | | N/A |
| R.2.2 | Measures to control faults/errors | | N/A |
| R.2.2.1 | When redundant memory with comparison is provided on two areas of the same component, the data in one area is stored in a different format from that in the other area | | N/A |
| R.2.2.2 | Programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.2 and that use dual channel structures with comparison, have additional fault/error detection means for any fault/errors not detected by the comparison | | N/A |
| R.2.2.3 | For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, means are provided for the recognition and control of errors in transmissions to external safety-related data paths | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| R.2.2.4 | For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the programmable electronic circuits incorporate measures to address the fault/errors in safety-related segments and data indicated in table R.1 and R.2 as appropriate | | N/A |
| R.2.2.5 | For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, detection of a fault/error occur before compliance with clause 19 is impaired | | N/A |
| R.2.2.6 | The software is referenced to relevant parts of the operating sequence and the associated hardware functions | | N/A |
| R.2.2.7 | Labels used for memory locations are unique | | N/A |
| R.2.2.8 | The software is protected from user alteration of safety-related segments and data | | N/A |
| R.2.2.9 | Software and safety-related hardware under its control is initialized and terminates before compliance with clause 19 is impaired | | N/A |
| R.3 | Measures to avoid errors | | N/A |
| R.3.1 | General | | N/A |
| | For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the following measures to avoid systematic fault in the software are applied | | N/A |
| | Software that incorporates measures used to control the fault/error conditions specified in table R.2 is inherently acceptable for software required to control the fault/error conditions specified in table R.1 | | N/A |
| R.3.2 | Specification | | N/A |
| R.3.2.1 | Software safety requirements: | Software Id: | N/A |
| | The specification of the software safety requirements includes the descriptions listed | | N/A |
| R.3.2.2 | Software architecture | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| R.3.2.2.1 | The specification of the software architecture includes the aspects listed <ul style="list-style-type: none"> - techniques and measures to control software faults/errors (refer to R.2.2); - interactions between hardware and software; - partitioning into modules and their allocation to the specified safety functions; - hierarchy and call structure of the modules (control flow); - interrupt handling; - data flow and restrictions on data access; - architecture and storage of data; - time-based dependencies of sequences and data | Document ref. No: | N/A |
| R.3.2.2.2 | The architecture specification is validated against the specification of the software safety requirements by static analysis | | N/A |
| R.3.2.3 | Module design and coding | | N/A |
| R.3.2.3.1 | Based on the architecture design, software is suitably refined into modules | | N/A |
| | Software module design and coding is implemented in a way that is traceable to the software architecture and requirements | | N/A |
| R.3.2.3.2 | Software code is structured | | N/A |
| R.3.2.3.3 | Coded software is validated against the module specification by static analysis | | N/A |
| | The module specification is validated against the architecture specification by static analysis | | N/A |
| R.3.3.3 | Software validation | | N/A |
| | The software is validated with reference to the requirements of the software safety requirements specification | | N/A |
| | Compliance is checked by simulation of: | | N/A |
| | - input signals present during normal operation | | N/A |
| | - anticipated occurrences | | N/A |
| | - undesired conditions requiring system action | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| TABLE R.1 ^e – GENERAL FAULT/ERROR CONDITIONS | | | | | | |
|---|---|---|--|--|-------------------------------------|---------|
| Component ^a | Fault/error | Acceptable measures ^{b, c} | Definitions | Document reference for applied measure | Document reference for applied test | Verdict |
| 1 CPU | | | | | | N/A |
| 1.1 Registers | Stuck at | Functional test, or periodic self-test using either: <ul style="list-style-type: none"> - static memory test, or - word protection with single bit redundancy | H.2.16.5 H.2.16.6 H.2.19.6 H.2.19.8.2 | | | N/A |
| 1.2 VOID | | | | | | |
| 1.3 Programme counter | Stuck at | Functional test, or Periodic self-test, or Independent time-slot monitoring, or Logical monitoring of the programme sequence | H.2.16.5 H.2.16.6 H.2.18.10.4 H.2.18.10.2 | | | N/A |
| 2 Interrupt handling and execution | No interrupt or too frequent interrupt | Functional test, or time-slot monitoring | H.2.16.5 H.2.18.10.4 | | | N/A |
| 3 Clock | Wrong frequency (for quartz synchronized clock: harmonics/sub-harmonics only) | Frequency monitoring, or time slot monitoring | H.2.18.10.1 H.2.18.10.4 | | | N/A |
| 4. Memory | | | | | | N/A |
| 4.1 Invariable memory | All single bit faults | Periodic modified checksum, or multiple checksum, or word protection with single bit redundancy | H.2.19.3.1 H.2.19.3.2 H.2.19.8.2 | | | N/A |
| 4.2 Variable memory | DC fault | Periodic static memory test, or word protection with single bit redundancy | H.2.19.6 H.2.19.8.2 | | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| TABLE R.1 ^e – GENERAL FAULT/ERROR CONDITIONS | | | | | | |
|---|---|---|---|--|-------------------------------------|---------|
| Component ^a | Fault/error | Acceptable measures ^{b, c} | Definitions | Document reference for applied measure | Document reference for applied test | Verdict |
| 4.3 Addressing (relevant to variable and invariable memory) | Stuck at | Word protection with single bit redundancy including the address | H.2.19.8.2 | | | N/A |
| 5 Internal data path | Stuck at | Word protection with single bit redundancy | H.2.19.8.2 | | | N/A |
| 5.1 VOID | | | | | | |
| 5.2 Addressing | Wrong address | Word protection with single bit redundancy including the address | H.2.19.8.2 | | | N/A |
| 6 External communication | Hamming distance 3 | Word protection with multi-bit redundancy, or CRC – single work, or Transfer redundancy, or Protocol test | H.2.19.8.1 H.2.19.4.1 H.2.18.2.2 H.2.18.14 | | | N/A |
| 6.1 VOID | | | | | | |
| 6.2 VOID | | | | | | |
| 6.3 Timing | Wrong point in time Wrong sequence | Time-slot monitoring, or scheduled transmission Time-slot and logical monitoring, or comparison of redundant communication channels by either: - reciprocal comparison - independent hardware comparator Logical monitoring, or time-slot monitoring, or Scheduled transmission | H.2.18.10.4 H.2.18.18 H.2.18.10.3 H.2.18.15 H.2.18.3 H.2.18.10.2 H.2.18.10.4 H.2.18.18 | | | N/A |
| 7 Input/output periphery | Fault conditions specified in 19.11.2 | Plausibility check | H.2.18.13 | | | N/A |

| IEC 60335-2-29 | | | |
|----------------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| TABLE R.1 ^e – GENERAL FAULT/ERROR CONDITIONS | | | | | | |
|--|--|-------------------------------------|-------------|--|-------------------------------------|---------|
| Component ^a | Fault/error | Acceptable measures ^{b, c} | Definitions | Document reference for applied measure | Document reference for applied test | Verdict |
| 7.1 VOID | | | | | | |
| 7.2 Analog I/O | | | | | | N/A |
| 7.2.1 A/D and D/A- converter | Fault conditions specified in 19.11.2 | Plausibility check | H.2.18.13 | | | N/A |
| 7.2.2 Analog multiplexer | Wrong addressing | Plausibility check | H.2.18.13 | | | N/A |
| 8 VOID | | | | | | |
| 9 Custom chips ^d e.g. ASIC, GAL, gate array | Any output outside the static and dynamic functional specification | Periodic self-test | H.2.16.6 | | | N/A |
| NOTE A Stuck-at fault model denotes a fault model representing an open circuit or a non-varying signal level. A DC fault model denotes a stuck-at fault model incorporating short circuit between signal lines. | | | | | | |
| ^{a)} For fault/error assessment, some components are divided into their sub-functions. ^{b)} For each sub-function in the table, the Table R.2 measure will cover the software fault/error. ^{c)} Where more than one measure is given for a sub-function, these are alternatives. ^{d)} To be divided as necessary by the manufacturer into sub-functions. ^{e)} Table R.1 is applied according to the requirements of R.1 to R.2.2.9 inclusive. | | | | | | |

| | | | |
|-------|---|--|-----|
| AA | ANNEX AA (NORMATIVE) BATTERY CHARGERS FOR USE BY CHILDREN (IEC 60335-2-29/A1) | | N/A |
| | Battery chargers intended to be used by children at least eight years old without supervision shall comply with this standard but as modified by this annex. The battery charger have a d.c. output at SELV not exceeding 30 V and a rated output not exceeding 50 VA | | N/A |
| 5 | GENERAL CONDITIONS FOR THE TESTS | | N/A |
| 5.201 | When batteries are used, the generally available rechargeable batteries giving the most unfavourable conditions are used | | N/A |
| 6.1 | Battery chargers suitable for outdoor use shall be class III | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Other battery chargers shall be class II or class III | | N/A |
| 6 | CLASSIFICATION | | N/A |
| 6.2 | Battery chargers suitable for outdoor use shall be at least IPX7 | | N/A |
| 6.201 | Enclosures shall be classified at least IP3X with regard to protection against ingress of solid foreign objects. | | N/A |
| 7 | MARKING AND INSTRUCTIONS | | N/A |
| 7.1 | Symbol 5957 of IEC 60417 or text "For indoor use only" for battery chargers for indoor use | | N/A |
| | IP number | | N/A |
| | Smiling face symbol together with 8+ | | N/A |
| 7.6 | Correct symbols used | | N/A |
| 7.12 | Instructions for safe use contains: | | N/A |
| | - Warning to only allow children at least 8 years old to use battery charger | | N/A |
| | - Sufficient instructions for safe use of battery charger by a child | | N/A |
| | - Explanation that battery charger is not a toy | | N/A |
| | - Instruction for child not to try and recharge non-rechargeable batteries | | N/A |
| | - Warning to examine battery charger regularly for damage | | N/A |
| | - Warning in case battery charger is damaged | | N/A |
| | Instruction for Class III battery charger to be supplied from transformer for toys | | N/A |
| 7.14 | Height of symbol marked on the appliance at least 10 mm | | N/A |
| | Height of lettering at least 3 mm | | N/A |
| 8 | PROTECTION AGAINST ACCESS TO LIVE PARTS | | N/A |
| 8.1.1 | Use of test probe B of IEC 61032: no contact with live parts or metal parts separated from live parts by basic insulation only, even after use of a tool to remove parts of enclosure | | N/A |
| 10 | POWER INPUT AND CURRENT | | N/A |
| 10.101 | The output voltage not exceed 42,4 V peak | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|------------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 11 | HEATING | | N/A |
| 11.8 | Temperature rises of parts that can be touched by test probe 18 of IEC 61032 | | N/A |
| | - 25 K, if of metal; | | N/A |
| | - 35 K, if of other material. | | N/A |
| 17 | OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS | | N/A |
| | Temperature rises of parts that can be touched by test probe 18 of IEC 61032 | | N/A |
| | - 45 K, if of metal; | | N/A |
| | - 55 K, if of other material. | | N/A |
| 19 | ABNORMAL OPERATION | | N/A |
| 19.13 | Temperature rises of parts that can be touched by test probe 18 of IEC 61032 | | N/A |
| | - 45 K, if of metal; | | N/A |
| | - 55 K, if of other material. | | N/A |
| 21 | MECHANICAL STRENGTH | | N/A |
| 21.201 | Impact test Eha of IEC 60068-2-75, with impact energy of 2 J | | N/A |
| | For rectangular shaped battery chargers, the four sides and four edges are subjected to an impact. For other battery chargers, the enclosure is subjected to eight impacts equally spaced over the periphery. | | N/A |
| | Free fall test Ed, Procedure 1 of IEC 60068-2-32, from the height of 500 mm | | N/A |
| | Battery charger not damaged to such extent that compliance is impaired, live parts shall not become accessible | | N/A |
| 22 | CONSTRUCTION | | N/A |
| 22.201 | Battery charger with only one rated voltage or rated voltage range | | N/A |
| | Battery charger not incorporate means for manually adjusting output voltage | | N/A |
| 22.202 | Battery chargers shall be constructed so that reverse charging is prevented, regardless of the state of charge of the battery. This applies even if the battery is inserted with the wrong polarity. | | N/A |
| 24 | COMPONENTS | | N/A |

| IEC 60335-2-29 | | | |
|-----------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 24.201 | Transformer for toys tested in accordance with sub-clauses 7.2, 20.5.1 and 20.101 and clause 15 of standard IEC 61558-2-7 | | N/A |
| 25 | SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS | | N/A |
| 25.1 | Battery charger not provided with an appliance inlet | | N/A |
| 25.5 | Battery charger provided with type Y or type Z attachment | | N/A |

IEC 60335-2-29

| 10.1 | TABLE: Input power deviation | | | | | N/A |
|----------------------------|------------------------------|----------------|----------------|-------------------------|--------|-----|
| Input deviation of/at: | P rated (W) | P measured (W) | ΔP (%) | Required ΔP (%) | Remark | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| Supplementary information: | | | | | | |

| 10.2 | TABLE: Input current deviation | | | | | P |
|----------------------------------|--------------------------------|----------------|----------------|-------------------------|--------|---|
| Current deviation of/at: | I rated (A) | I measured (A) | ΔI (%) | Required ΔI (%) | Remark | |
| Model: SSLC084V42J (for E-load) | | | | | | |
| 100V 47Hz | 1.8 | 1.39 | -22.8% | +15% or 0.30A | -- | |
| 100V 63Hz | 1.8 | 1.39 | -22.8% | +15% or 0.30A | -- | |
| 240V 47Hz | 1.8 | 0.64 | -64.4% | +15% or 0.30A | -- | |
| 240V 63Hz | 1.8 | 0.64 | -64.4% | +15% or 0.30A | -- | |
| Model: SSLC084V42J (for Battery) | | | | | | |
| 100V 47Hz | 1.8 | 1.37 | -23.9% | +15% or 0.30A | -- | |
| 100V 63Hz | 1.8 | 1.37 | -23.9% | +15% or 0.30A | -- | |
| 240V 47Hz | 1.8 | 0.63 | -65.0% | +15% or 0.30A | -- | |
| 240V 63Hz | 1.8 | 0.63 | -65.0% | +15% or 0.30A | -- | |
| Model: SSLC058V29J (for E-load) | | | | | | |
| 100V 47Hz | 1.4 | 1.02 | -27.1% | +15% or 0.30A | -- | |
| 100V 63Hz | 1.4 | 1.02 | -27.1% | +15% or 0.30A | -- | |

IEC 60335-2-29

| 10.2 | TABLE: Input current deviation | | | | | P |
|----------------------------------|--------------------------------|----------------|----------------|-------------------------|--------|---|
| Current deviation of/at: | I rated (A) | I measured (A) | ΔI (%) | Required ΔI (%) | Remark | |
| 240V 47Hz | 1.4 | 0.47 | -66.4% | +15% or 0.30A | -- | |
| 240V 63Hz | 1.4 | 0.47 | -66.4% | +15% or 0.30A | -- | |
| Model: SSLC058V29J (for Battery) | | | | | | |
| 100V 47Hz | 1.4 | 1.02 | -27.1% | +15% or 0.30A | -- | |
| 100V 63Hz | 1.4 | 1.02 | -27.1% | +15% or 0.30A | -- | |
| 240V 47Hz | 1.4 | 0.47 | -66.4% | +15% or 0.30A | -- | |
| 240V 63Hz | 1.4 | 0.47 | -66.4% | +15% or 0.30A | -- | |

| 10.101 | TABLE: no-load d.c. output voltage measurements | | | P |
|--------------------|---|--|----------|--------|
| Test location | V_{NL} (V) | | Required | Remark |
| Model: SSLC084V42J | | | | |
| 100V/47Hz | 42.1 | | <42,4V | - |
| 100V/63Hz | 42.1 | | <42,4V | - |
| 240V/47Hz | 42.1 | | <42,4V | - |
| 240V/63Hz | 42.1 | | <42,4V | - |
| Model: SSLC058V29J | | | | |
| 100V/47Hz | 29.5 | | <42,4V | - |
| 100V/63Hz | 29.5 | | <42,4V | - |
| 240V/47Hz | 29.5 | | <42,4V | - |
| 240V/63Hz | 29.5 | | <42,4V | - |

| 10.102 | TABLE: Output current deviation | | | | | P |
|---------------------------------|---------------------------------|-----------------|--------------------|------------------|---------------------------|--------|
| Current deviation of/at: | U_o rated (V) | I_o rated (A) | I_o measured (A) | ΔI_o (%) | Required ΔI_o (%) | Remark |
| Model: SSLC084V42J (for E-load) | | | | | | |

IEC 60335-2-29

| 10.102 | TABLE: Output current deviation | | | | | | P |
|----------------------------------|---------------------------------|--------------------------|-----------------------------|---------------------|------------------------------|--------|---|
| Current deviation of/at: | U _o rated (V) | I _o rated (A) | I _o measured (A) | ΔI _o (%) | Required ΔI _o (%) | Remark | |
| 100V 47Hz | 42.0 | 2.0 | 1.84 | -8.0% | ±10% | -- | |
| 100V 63Hz | 42.0 | 2.0 | 1.84 | -8.0% | ±10% | -- | |
| 240V 47Hz | 42.0 | 2.0 | 1.84 | -8.0% | ±10% | -- | |
| 240V 63Hz | 42.0 | 2.0 | 1.84 | -8.0% | ±10% | -- | |
| Model: SSLC084V42J (for Battery) | | | | | | | |
| 100V 47Hz | 42.0 | 2.0 | 1.83 | -8.5% | ±10% | -- | |
| 100V 63Hz | 42.0 | 2.0 | 1.83 | -8.5% | ±10% | -- | |
| 240V 47Hz | 42.0 | 2.0 | 1.83 | -8.5% | ±10% | -- | |
| 240V 63Hz | 42.0 | 2.0 | 1.83 | -8.5% | ±10% | -- | |
| Model: SSLC058V29J (for E-load) | | | | | | | |
| 100V 47Hz | 29.4 | 2.0 | 1.87 | -6.5% | ±10% | -- | |
| 100V 63Hz | 29.4 | 2.0 | 1.87 | -6.5% | ±10% | -- | |
| 240V 47Hz | 29.4 | 2.0 | 1.87 | -6.5% | ±10% | -- | |
| 240V 63Hz | 29.4 | 2.0 | 1.87 | -6.5% | ±10% | -- | |
| Model: SSLC058V29J (for Battery) | | | | | | | |
| 100V 47Hz | 29.4 | 2.0 | 1.86 | -7.0% | ±10% | -- | |
| 100V 63Hz | 29.4 | 2.0 | 1.86 | -7.0% | ±10% | -- | |
| 240V 47Hz | 29.4 | 2.0 | 1.86 | -7.0% | ±10% | -- | |
| 240V 63Hz | 29.4 | 2.0 | 1.86 | -7.0% | ±10% | -- | |

| 11.8 | TABLE: Heating Test | | P |
|---|------------------------|--|-------------------------------------|
| | Test voltage (V) | See table below | — |
| | Ambient (°C) | See table below | — |
| Thermocouple Locations | | Max. temperature rise measured, ΔT (K) | Max. temperature rise limit, ΔT (K) |
| Model: SSLC084V42J, 1.06 x 100V =106V at 47Hz, t1:21.2 t2:21.3 with E-load | | | |
| Pin of inlet | | 33.5 | 45 |
| Plastic of inlet | | 50.2 | Cl.30 |
| PCB surface | | 59.5 | Cl.30 |
| Electrolytic capacitor (C1) | | 65.0 | T105-25=80 |

| IEC 60335-2-29 | | |
|---|------|------------|
| X2 capacitor (CX1) | 51.8 | T100-25=75 |
| X2 capacitor (CX2) | 30.5 | T100-25=75 |
| Y capacitor (CY1) | 35.8 | T85-25=60 |
| Y capacitor (CY2) | 35.4 | T85-25=60 |
| Y capacitor (CY3) | 36.1 | T85-25=60 |
| Y capacitor (CY4) | 29.1 | T85-25=60 |
| Coil (FL1) | 93.5 | 115 |
| Varistor (RV1) | 29.2 | T85-25=60 |
| Optocoupler | 58.6 | T110-25=85 |
| Primary winding of transformer | 72.8 | 85 |
| Secondary winding of transformer | 71.5 | 85 |
| Output cord (junction point) | 16.3 | 50 |
| Plastic enclosure (outside) | 19.3 | 60 |
| Plastic enclosure (Inside) | 38.3 | Cl.30 |
| Test corner | 36.3 | 65 |
| Model: SSLC084V42J, 1.06 x 240V =254.4V at 63Hz, t1:20.8 t2:20.9 with E-load | | |
| Pin of inlet | 28.0 | 45 |
| Plastic of inlet | 36.9 | Cl.30 |
| PCB surface | 69.7 | Cl.30 |
| Electrolytic capacitor (C1) | 59.6 | T105-25=80 |
| X2 capacitor (CX1) | 35.2 | T100-25=75 |
| X2 capacitor (CX2) | 22.1 | T100-25=75 |
| Y capacitor (CY1) | 44.4 | T85-25=60 |
| Y capacitor (CY2) | 38.8 | T85-25=60 |
| Y capacitor (CY3) | 28.7 | T85-25=60 |
| Y capacitor (CY4) | 26.2 | T85-25=60 |
| Coil (FL1) | 62.2 | 115 |
| Varistor (RV1) | 21.3 | T85-25=60 |
| Optocoupler | 57.3 | T110-25=85 |
| Primary winding of transformer | 71.9 | 85 |
| Secondary winding of transformer | 72.0 | 85 |
| Output cord (junction point) | 22.8 | 50 |

| IEC 60335-2-29 | | |
|---|------|------------|
| Plastic enclosure (outside) | 30.2 | 60 |
| Plastic enclosure (Inside) | 49.6 | Cl.30 |
| Test corner | 48.2 | 65 |
| Model: SSLC084V42J, 1.06 x 100V =106V at 47Hz, t1:21.1 t2:21.1 (Connected to battery) | | |
| Pin of inlet | 31.8 | 45 |
| Plastic of inlet | 43.9 | Cl.30 |
| PCB surface | 54.3 | Cl.30 |
| Electrolytic capacitor (C1) | 57.1 | T105-25=80 |
| X2 capacitor (CX1) | 44.5 | T100-25=75 |
| X2 capacitor (CX2) | 29.2 | T100-25=75 |
| Y capacitor (CY1) | 37.5 | T85-25=60 |
| Y capacitor (CY2) | 36.7 | T85-25=60 |
| Y capacitor (CY3) | 33.9 | T85-25=60 |
| Y capacitor (CY4) | 29.9 | T85-25=60 |
| Coil (FL1) | 87.6 | 115 |
| Varistor (RV1) | 28.3 | T85-25=60 |
| Optocoupler | 51.8 | T110-25=85 |
| Primary winding of transformer | 61.3 | 85 |
| Secondary winding of transformer | 60.5 | 85 |
| Output cord (junction point) | 21.2 | 50 |
| Plastic enclosure (outside) | 28.7 | 60 |
| Plastic enclosure (Inside) | 38.6 | Cl.30 |
| Test corner | 36.9 | 65 |
| Model: SSLC084V42J, 1.06 x 240V =254.4V at 63Hz, t1:21.9 t2:22.0 (Connected to battery) | | |
| Pin of inlet | 22.4 | 45 |
| Plastic of inlet | 30.1 | Cl.30 |
| PCB surface | 60.0 | Cl.30 |
| Electrolytic capacitor (C1) | 50.8 | T105-25=80 |
| X2 capacitor (CX1) | 32.9 | T100-25=75 |
| X2 capacitor (CX2) | 21.0 | T100-25=75 |
| Y capacitor (CY1) | 41.6 | T85-25=60 |
| Y capacitor (CY2) | 36.5 | T85-25=60 |

| IEC 60335-2-29 | | |
|--|------|------------|
| Y capacitor (CY3) | 27.0 | T85-25=60 |
| Y capacitor (CY4) | 24.6 | T85-25=60 |
| Coil (FL1) | 57.7 | 115 |
| Varistor (RV1) | 20.4 | T85-25=60 |
| Optocoupler | 54.4 | T110-25=85 |
| Primary winding of transformer | 67.3 | 85 |
| Secondary winding of transformer | 67.3 | 85 |
| Output cord (junction point) | 21.7 | 50 |
| Plastic enclosure (outside) | 29.0 | 60 |
| Plastic enclosure (Inside) | 38.9 | Cl.30 |
| Test corner | 35.5 | 65 |
| Model: SSLC058V29J, 1.06 x 100V =106V at 47Hz, t1:21.6 t2:21.9 (with E-load) | | |
| Pin of inlet | 6.2 | 45 |
| Plastic of inlet | 7.7 | Cl.30 |
| PCB surface | 19.1 | Cl.30 |
| Electrolytic capacitor (C1) | 13.8 | T105-25=80 |
| X2 capacitor (CX1) | 8.2 | T100-25=75 |
| X2 capacitor (CX2) | 9.8 | T100-25=75 |
| Y capacitor (CY1) | 10.5 | T85-25=60 |
| Y capacitor (CY2) | 9.7 | T85-25=60 |
| Y capacitor (CY3) | 6.5 | T85-25=60 |
| Y capacitor (CY4) | 5.8 | T85-25=60 |
| Coil (FL1) | 15.0 | 115 |
| Varistor (RV1) | 4.6 | T85-25=60 |
| Optocoupler | 17.9 | T110-25=85 |
| Primary winding of transformer | 19.5 | 85 |
| Secondary winding of transformer | 20.0 | 85 |
| Output cord (junction point) | 4.8 | 50 |
| Plastic enclosure (outside) | 6.2 | 60 |
| Plastic enclosure (Inside) | 15.6 | Cl.30 |
| Test corner | 12.7 | 65 |
| Model: SSLC058V29J, 1.06 x 240V =254.4V at 63Hz, t1:22.7 t2:22.4 (with E-load) | | |

| IEC 60335-2-29 | | |
|---|------|------------|
| Pin of inlet | 13.0 | 45 |
| Plastic of inlet | 17.3 | Cl.30 |
| PCB surface | 41.9 | Cl.30 |
| Electrolytic capacitor (C1) | 31.9 | T105-25=80 |
| X2 capacitor (CX1) | 19.6 | T100-25=75 |
| X2 capacitor (CX2) | 25.9 | T100-25=75 |
| Y capacitor (CY1) | 27.5 | T85-25=60 |
| Y capacitor (CY2) | 23.8 | T85-25=60 |
| Y capacitor (CY3) | 15.9 | T85-25=60 |
| Y capacitor (CY4) | 14.5 | T85-25=60 |
| Coil (FL1) | 35.7 | 115 |
| Varistor (RV1) | 10.7 | T85-25=60 |
| Optocoupler | 37.6 | T110-25=85 |
| Primary winding of transformer | 47.3 | 85 |
| Secondary winding of transformer | 48.3 | 85 |
| Output cord (junction point) | 15.1 | 50 |
| Plastic enclosure (outside) | 16.6 | 60 |
| Plastic enclosure (Inside) | 29.6 | Cl.30 |
| Test corner | 27.0 | 65 |
| Model: SSLC058V29J, 1.06 x 100V =106V at 47Hz, t1:21.3 t2:21.2 (connected to Battery) | | |
| Pin of inlet | 21.2 | 45 |
| Plastic of inlet | 37.6 | Cl.30 |
| PCB surface | 53.4 | Cl.30 |
| Electrolytic capacitor (C1) | 49.3 | T105-25=80 |
| X2 capacitor (CX1) | 37.3 | T100-25=75 |
| X2 capacitor (CX2) | 33.2 | T100-25=75 |
| Y capacitor (CY1) | 34.9 | T85-25=60 |
| Y capacitor (CY2) | 33.5 | T85-25=60 |
| Y capacitor (CY3) | 29.9 | T85-25=60 |
| Y capacitor (CY4) | 26.3 | T85-25=60 |
| Coil (FL1) | 69.6 | 115 |
| Varistor (RV1) | 23.3 | T85-25=60 |

| |
|-----------------------|
| IEC 60335-2-29 |
|-----------------------|

| | | |
|---|------|------------|
| Optocoupler | 49.1 | T110-25=85 |
| Primary winding of transformer | 53.5 | 85 |
| Secondary winding of transformer | 56.5 | 85 |
| Output cord (junction point) | 19.0 | 50 |
| Plastic enclosure (outside) | 25.0 | 60 |
| Plastic enclosure (Inside) | 39.3 | Cl.30 |
| Test corner | 35.7 | 65 |
| Model: SSLC058V29J, 1.06 x 240V =254.4V at 63Hz, t1:20.1 t2:20.3 (connected to Battery) | | |
| Pin of inlet | 19.5 | 45 |
| Plastic of inlet | 26.7 | Cl.30 |
| PCB surface | 52.9 | Cl.30 |
| Electrolytic capacitor (C1) | 42.5 | T105-25=80 |
| X2 capacitor (CX1) | 28.6 | T100-25=75 |
| X2 capacitor (CX2) | 36.5 | T100-25=75 |
| Y capacitor (CY1) | 36.5 | T85-25=60 |
| Y capacitor (CY2) | 32.7 | T85-25=60 |
| Y capacitor (CY3) | 24.1 | T85-25=60 |
| Y capacitor (CY4) | 22.7 | T85-25=60 |
| Coil (FL1) | 47.0 | 115 |
| Varistor (RV1) | 18.7 | T85-25=60 |
| Optocoupler | 48.7 | T110-25=85 |
| Primary winding of transformer | 57.7 | 85 |
| Secondary winding of transformer | 58.4 | 85 |
| Output cord (junction point) | 22.1 | 50 |
| Plastic enclosure (outside) | 20.5 | 60 |
| Plastic enclosure (Inside) | 42.2 | Cl.30 |
| Test corner | 37.1 | 65 |

| | | |
|------|--|-----|
| 11.8 | TABLE: Heating test, resistance method | N/A |
| | Test voltage (V).....: | — |
| | Ambient, t ₁ (°C).....: | — |

IEC 60335-2-29

| Ambient, t_2 (°C).....: | | | | | — |
|-----------------------------|--------------------|--------------------|--------|-------------|------------------|
| Temperature rise of winding | R ₁ (Ω) | R ₂ (Ω) | ΔT (K) | Max. ΔT (K) | Insulation class |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Supplementary information: | | | | | |

| 13.2 | TABLE: Leakage current | P |
|-----------------------------------|---|---------------------------------|
| | Heating appliances: 1,15 x rated input (W).....: | -- |
| | Motor-operated and combined appliances: 1,06 x rated voltage (V).....: | 1.06 x 240V =254.4V |
| Leakage current between | | I (mA) Max. allowed I (mA) |
| Model: SSLC084V42J | | |
| Live/Neutral – enclosure | | 0.017 0.35 peak |
| Live/Neutral – output terminal(+) | | 0.131 0.35 peak |
| Live/Neutral – output terminal(-) | | 0.132 0.35 peak |
| Model: SSLC058V29J | | |
| Live/Neutral – enclosure | | 0.018 0.35 peak |
| Live/Neutral – output terminal(+) | | 0.142 0.35 peak |
| Live/Neutral – output terminal(-) | | 0.143 0.35 peak |

| 13.3 | TABLE: Electric strength | P |
|--|--------------------------|--|
| Test voltage applied between: | | Test potential applied (V) Breakdown / flashover (Yes/No) |
| Live/Neutral – enclosure | | 3000 No |
| Live/Neutral – output terminal | | 3000 No |
| Primary of transformer to secondary of transformer | | 3000 No |
| Live/Neutral – earthed part | | 1000 No |

IEC 60335-2-29

| 14 | TABLE: Transient overvoltages | | | | | N/A |
|----------------------------|-------------------------------|------------------|---------------------------|--------------------------|--------------------|-----|
| Clearance between: | CI (mm) | Required CI (mm) | Rated impulse voltage (V) | Impulse test voltage (V) | Flashover (Yes/No) | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| Supplementary information: | | | | | | |

| | | | | |
|--|--|---------------------|---------------------|---|
| 16.2 | TABLE: Leakage current | | | P |
| | Single phase appliances: 1,06 x rated voltage (V) : | 1.06 x 240V= 254.4V | | — |
| | Three phase appliances 1,06 x rated voltage divided by $\sqrt{3}$ (V)..... : | -- | | — |
| Leakage current between | | I (mA) | Max. allowed I (mA) | |
| Model: SSLC084V42J | | | | |
| Live/Neutral – enclosure | | 0.018 | 0.25 | |
| Live/Neutral – output terminal(+) | | 0.210 | 0.25 | |
| Live/Neutral – output terminal(-) | | 0.211 | 0.25 | |
| Model: SSLC058V29J | | | | |
| Live/Neutral – enclosure | | 0.018 | 0.25 | |
| Live/Neutral – output terminal(+) | | 0.221 | 0.25 | |
| Live/Neutral – output terminal(-) | | 0.222 | 0.25 | |
| Supplementary information: After test of cl.15.3 and with protective impedance disconnected. | | | | |

| 16.3 | TABLE: Dielectric strength | | P |
|--|----------------------------|--------------------------------|---|
| Test voltage applied between: | Test potential applied (V) | Breakdown / flashover (Yes/No) | |
| Live/Neutral – enclosure | 3000 | No | |
| Live/Neutral – output terminal | 3000 | No | |
| Primary of transformer to secondary of transformer | 3000 | No | |
| Live/Neutral – earthed part | 1250 | No | |

IEC 60335-2-29

| | | | | |
|---|----------------------------|--|---|---|
| 17 | TABLE: Overload protection | | | P |
| Thermocouple locations | | Max. temperature rise measured, ΔT (K) | Max. temperature rise limit, ΔT (K) | |
| Model: SSLC084V42J, transformer: SSB3225-36GS | | | | |
| Primary winding of transformer | | 45.5 | 175-25=150 | |
| Secondary winding of transformer | | 52.5 | 175-25=150 | |
| SELV wires | | 21.2 | 50+15=65 | |
| Model: SSLC058V29J, transformer: SSB3225-24GS | | | | |
| Primary winding of transformer | | 57.8 | 175-25=150 | |
| Secondary winding of transformer | | 68.6 | 175-25=150 | |
| SELV wires | | 45.4 | 50+15=65 | |

| | | | | | |
|----------------------------|---|--------------------|----------------|--------|-------------|
| 17 | TABLE: Overload protection, resistance method | | | | N/A |
| Test voltage (V) | | | | — | |
| Ambient, t_1 (°C)..... | | | | — | |
| Ambient, t_2 (°C)..... | | | | — | |
| Temperature of winding | R_1 (Ω) | R_2 (Ω) | ΔT (K) | T (°C) | Max. T (°C) |
| | | | | | |
| | | | | | |
| | | | | | |
| Supplementary information: | | | | | |

| | | | |
|---|-------------------------------|------------------------|---|
| 19 | Abnormal operation conditions | | P |
| Operational characteristics | YES/NO | Operational conditions | |
| Are there electronic circuits to control the appliance operation? | No | N/A | |
| Are there “off” or “stand-by” position? | No | N/A | |
| The unintended operation of the appliance results in dangerous malfunction? | No | N/A | |

IEC 60335-2-29

| Sub-clause | Operating conditions description | Test results description | PEC description | EMP 19.11.4 | Software type required | 19.11.3 PEC | Final result |
|------------|----------------------------------|--------------------------|-----------------|-------------|------------------------|-------------|--------------|
| 19.2 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.3 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.4 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.5 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.6 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.7 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.8 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.9 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.10 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.11.2 | 240V | N/A | N/A | N/A | N/A | N/A | P |
| 19.11.4.8 | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 19.102 | 240V | N/A | N/A | N/A | N/A | N/A | P |
| 19.10x | N/A | N/A | N/A | N/A | N/A | N/A | N/A |

Supplementary information:

| | | | | | | |
|------|--|---|--------------------|--------------------|--------|-------------|
| 19.7 | TABLE: Abnormal operation, locked rotor/moving parts | | | | | N/A |
| | Test voltage (V) | : | | | | — |
| | Ambient, t ₁ (°C) | : | | | | — |
| | Ambient, t ₂ (°C) | : | | | | — |
| | Temperature of winding | | R ₁ (Ω) | R ₂ (Ω) | ΔT (K) | T (°C) |
| | | | | | | Max. T (°C) |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Supplementary information:

| | | | | | | |
|------|---|---|--|--|--|-----|
| 19.9 | TABLE: Abnormal operation, running overload | | | | | N/A |
| | Test voltage (V) | : | | | | — |
| | Ambient, t ₁ (°C) | : | | | | — |
| | Ambient, t ₂ (°C) | : | | | | — |

IEC 60335-2-29

| Temperature of winding | R ₁ (Ω) | R ₂ (Ω) | ΔT (K) | T (°C) | Max. T (°C) |
|------------------------|--------------------|--------------------|--------|--------|-------------|
| | | | | | |
| | | | | | |
| | | | | | |

Supplementary information:

| 19.13 | TABLE: Abnormal operation, temperature rises | | | N/A |
|------------------------|--|--|-------------------------------------|-----|
| Thermocouple locations | Max. temperature rise measured, ΔT (K) | | Max. temperature rise limit, ΔT (K) | |
| | | | | |
| | | | | |
| | | | | |

Supplementary information:

| 21.1 | TABLE: Impact resistance | | | P |
|---------------------|--------------------------|--------------------|----------|---|
| Impacts per surface | Surface tested | Impact energy (Nm) | Comments | |
| Enclosure | Three brows | 1.0J±0.05J | P | |
| | | | | |
| | | | | |

Supplementary information:

| 24.1 | TABLE: Components | | | | | P |
|-------------------|--|--------------|-----------------------|---------------|-------------------------------------|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹⁾ | |
| Plug | Shangyu Jintao Electron Co., Ltd. | JT003 | AC 250V, 16A | VDE 0620-1 | VDE 40021286 | |
| Alternative | Hong Shan Chuan Industry (Shen Zhen) Co., Ltd. | HSC-402 | AC 250V, 16A | VDE 0620-1 | VDE 40021749 | |
| Power cord | Shangyu Jintao Electron Co., Ltd. | H03VV-F | 3G0.75mm ² | EN 50525-2-11 | VDE 40013419 | |

IEC 60335-2-29

| 24.1 | TABLE: Components | | | | | P |
|----------------------|--|--------------|------------------------------|--------------------------|--|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹⁾ | |
| Alternative | Shenzhen Baohing Electric Wire & Cable Manufacture Co., Ltd. | H03VV-F | 3G0.75mm ² | EN 50525-2-11 | VDE 131689 | |
| Alternative | Shenzhen Baohing Electric Wire & Cable Manufacture Co., Ltd. | H05VV-F | 3G0.75mm ² | EN 50525-2-11 | VDE 131689 | |
| Connector | Shangyu Jintao Electron Co., Ltd. | JT-ST2B | AC 250V, 2.5A | EN 60320-1 | VDE 40027440 | |
| Alternative | Guangdong Xiongrun Electrical Co., Ltd. | XR-508 | AC 250V, 2.5A | EN 60320-1 | VDE 40012075 | |
| Appliance inlet | Zhe Jiang Bei Er Jia Electronic Co., Ltd. | ST-A04-001 | AC 250V, 2.5A | EN 60320-1 | VDE 40016045 | |
| Alternative | Rong Feng Industrial Co., Ltd. | RF-180 | AC 250V, 2.5A | EN 60320-1 | VDE 40030168 | |
| Fuse | Shenzhen Lanson Electronics Co. Ltd. | 5 N - Series | AC 250V, 3.15A, T | EN 60127-1 EN 60127-2 | VDE 40019482 | |
| Alternative | Dongguan Better Electronics Technology Co., Ltd. | 523-Serie(s) | AC 250V, 3.15A, F | EN 60127-1 EN 60127-2 | VDE 40025669 | |
| Varistor | Hongzhi Enterprises Ltd. | HEL-7D471K | AC 2500V, T85 | EN 61051 | VDE 40008621 | |
| Alternative | Shantou High-New Technology Dev. Zone Songtian Enterprise Co., Ltd. | STE-07D471K | AC 2500V, T85 | EN 61051 | VDE 40023049 | |
| Alternative | Nanjing Shagon Electronic Co., Ltd. | MYG07K471 | AC 2500V, T85 | EN 61051-1 | TUV SUD Z1 12 03 79712 001 | |
| X-Capacitor (CX1) | Tenta Electric Industrial Co., Ltd. | MEX | AC 275V, 0.47µF, X2, T100 | EN 60384-14 | VDE 119119 | |
| Alternative | Farad Electronics Co. Ltd. | PXK | AC 275V, 0.47µF, X2, T110 | EN 60384-14 | VDE 40030152 | |

| |
|-----------------------|
| IEC 60335-2-29 |
|-----------------------|

| 24.1 | TABLE: Components | | | | | P |
|-----------------------------------|--|--------------|---|--------------|--|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹⁾ | |
| X-Capacitor (CX2) | Tenta Electric Industrial Co., Ltd. | MEX | AC 275V, 0.1µF, X2, T100 | EN 60384-14 | VDE 119119 | |
| Alternative | Farad Electronics Co. Ltd. | PXK | AC 275V, 0.1µF, X2, T110 | EN 60384-14 | VDE 40030152 | |
| Y-Capacitor (CY1, CY2, CY5) | Success Electronics Co., Ltd. | SE | AC 250V, 4700pF, Y1, T125 | EN 60384-14 | VDE 40020002 | |
| Alternative | Kunshan Micro Capacitors Electronic Co., Ltd. | E-Series | AC 250V, 4700pF, Y1, T125 | EN 60384-14 | VDE 40016537 | |
| Alternative | Yinan Don's Electronic Component Co., Ltd. | CT81 | AC 250V, 4700pF, Y1, T125 | EN 60384-14 | VDE 135256 | |
| Alternative | Hsuan Tai Electronic Co. Ltd. | CY | AC 400V, 4700pF, Y1, T125 | EN 60384-14 | VDE 40008912 | |
| Y-Capacitor (CY3, CY4) | Success Electronics Co., Ltd. | SB | AC 250V, 470pF, Y2, T125 | EN 60384-14 | VDE 40016621 | |
| Alternative | Yinan Don's Electronic Components Co., Ltd. | CT81 | AC 250V, 470pF, Y2, T125 | EN 60384-14 | VDE 135256 | |
| Alternative | Ease Electronics Co., Ltd. | SY | AC 250V, 470pF, Y2, T85 | EN 60384-14 | VDE 40021868 | |
| Alternative | Haohua Electronic Co., | CT7 | AC 250V, 470pF, Y2, T125 | EN 60384-14 | VDE 40013601 | |
| Photo coupler | Sharp Corporation Electronic Components and Devices Group | PC817 | Int. cr: >7.6mm, Ext. cr: >7.6mm, Dti: >0.4mm, T110 | EN 60747-5-2 | VDE 40008087 | |
| Alternative | Lite-On Technology Corporation | LTV-817 | Int. cr: >7mm, Ext. cr: >7mm, Dti: >0.4mm, T110 | EN 60747-5-2 | VDE 40015248 | |
| Alternative | Everlight Electronics Co., Ltd. | EL817 V | Int. cr: >7.6mm, Ext. cr: >7.6mm, Dti: >0.4mm, T110 | EN 60747-5-2 | VDE 132249 | |

IEC 60335-2-29

| 24.1 | TABLE: Components | | | | | P |
|---|--|-------------------------|--|-----------------------------|--|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹⁾ | |
| Transformer (for model SSLC058V29J) | BORUN Electronics Factory | SSB058V29- ER35-JYGS | Pri.: N1:Φ0.2*10, 19Ts; N2:Φ0.25*2, 9Ts; N5:Φ0.2*10, 19Ts Sec.: N3:Φ0.20*20, 12Ts; N4:Φ0.25*2, 8Ts 425uH, Class 130 | EN 60335-1 EN 60335-2-29 | Tested with appliance | |
| Transformer (for model SSLC084V42J) | BORUN Electronics Factory | SSB084V42- ER35-JYGS | Pri.: N1:Φ0.2*10, 19Ts; N2:Φ0.25*2, 9Ts; N5:Φ0.2*10, 19Ts Sec.: N3:Φ0.20*20, 16Ts; N4:Φ0.25*2, 8Ts 330uH, Class 130 | EN 60335-1 EN 60335-2-29 | Tested with appliance | |
| - Bobbin | CHANG CHUN PLASTICS CO LTD | T375HF | PMC, V-0, 150°C | -- | UL E59481 | |
| - Magnet wire | JIANGYIN DOUBLE FEATHER CABLE CO LTD | 2UEW | 130°C | -- | UL E320132 | |
| Alternative | WUXI TAIHU COPPER MATERIAL WORKS | 2UEW | 155°C | -- | UL E231066 | |
| - Tube | SHENZHEN WOER HEAT- SHRINKABLE MATERIAL CO LTD | WF | 600V, 200°C, VW-1 | -- | UL E203950 | |
| - Insulation Tape | JINGJIANG JINGYANG INSULATING PRODUCT CO LTD | JY-133 | 130°C | -- | UL E309872 | |
| Output Cord | Shangyu Jintao Electron Co., Ltd. | H03VV-F | 2x0.75mm ² | EN 50525-2-11 | VDE 40013419 | |
| Alternative | Shangyu Jintao Electron Co., Ltd. | H03VVH2-F | 2x0.75mm ² | EN 50525-2-11 | VDE 40013419 | |

IEC 60335-2-29

| 24.1 | TABLE: Components | | | | | P |
|---|--|--------------|---|-----------------------------|--|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹⁾ | |
| Alternative | Shenzhen Bao Hing Electric Wire & Cable Manufacture Co. Ltd. | H03VV-F | 2x0.75mm ² | EN 50525-2-11 | VDE 131689 | |
| PCB | CHANGZHOU SHUANGJIN ELECTRONIC CO LTD | CCEM-1 | V-0, 130°C | EN 60335-1 EN 60335-2-29 | UL E190089 Tested with appliance | |
| Alternative | CHANGZHOU ZIYIN ELECTRONIC CIRCUIT CO LTD | CY-10 | V-0, 130°C | EN 60335-1 EN 60335-2-29 | UL E148151 Tested with appliance | |
| Enclosure | SABIC INNOVATIVE PLASTICS B V | 945 (GG) | PC, V-0 120°C, Min. 1.5mm thickness | EN 60335-1 EN 60335-2-29 | UL E45329 Tested with appliance | |
| Supplementary information: | | | | | | |
| 1) Provided evidence ensures the agreed level of compliance. See OD-CB2039. | | | | | | |

| 28.1 | TABLE: Threaded part torque test | | | P |
|------------------------------|----------------------------------|----------------------------------|---------------------|---|
| Threaded part identification | Diameter of thread (mm) | Column number (I, II, or III) | Applied torque (Nm) | |
| Screw for fixing enclosure | 2.9 | II | 0.5 | |
| Supplementary information: | | | | |

| 29.1 | TABLE: Clearances | | | | | P |
|----------------------------|--------------------------------|---------------------|--------------------|-----------------|-----------------|------------------|
| | Overvoltage category: II | | | | — | |
| | | Type of insulation: | | | | |
| Rated impulse voltage (V): | Min. cl (mm) | Basic (mm) | Supplementary (mm) | Reinforced (mm) | Functional (mm) | Verdict / Remark |
| 330 | 0,2* / 0,5 / 0,8** | N/A | N/A | N/A | N/A | N/A |
| 500 | 0,2* / 0,5 / 0,8** | N/A | N/A | N/A | N/A | N/A |
| 800 | 0,2* / 0,5 / 0,8** | N/A | N/A | N/A | N/A | N/A |
| 1 500 | 0,5 / 0,8** / 1,0*** | N/A | N/A | N/A | N/A | N/A |

| |
|-----------------------|
| IEC 60335-2-29 |
|-----------------------|

| | | |
|------|--------------------------------|---|
| 29.1 | TABLE: Clearances | P |
| | Overvoltage category: II | — |

| Rated impulse voltage (V): | Min. cl (mm) | Type of insulation: | | | | Verdict / Remark |
|----------------------------|----------------|---------------------|--------------------|-----------------|-----------------|------------------|
| | | Basic (mm) | Supplementary (mm) | Reinforced (mm) | Functional (mm) | |
| 2 500 | 1,5 / 2,0*** | 4.2 | 3.6 | N/A | 2.6 | P |
| 4 000 | 3,0 / 3,5*** | N/A | N/A | 6.5 | N/A | P |
| 6 000 | 5,5 / 6,0*** | N/A | N/A | N/A | N/A | N/A |
| 8 000 | 8,0 / 8,5*** | N/A | N/A | N/A | N/A | N/A |
| 10 000 | 11,0 / 11,5*** | N/A | N/A | N/A | N/A | N/A |

Supplementary information:

*) For tracks on printed circuit boards if pollution degree 1 and 2

**) For pollution degree 3

***) If the construction is affected by wear, distortion, movement of the parts or during assembly

Basic 1):

Difference pin of Y capacitors(CY1), Cr=Cl=4.2mm

Functional 2):

L/N in front of current fuse, Cr=Cl=2.6mm

Supplementary 3):

Difference pin of Y capacitors (CY2), Cr=Cl=3.6mm

Reinforce 4):

Primary winding to secondary winding (min), Cr=Cl=7.0mm

Primary circuit to secondary circuit (min), Cr=Cl=8.1mm

Primary circuit to accessible enclosure (min), Cr=Cl=6.5mm

| | | |
|------|---|---|
| 29.2 | TABLE: Creepage distances, basic, supplementary and reinforced insulation | P |
|------|---|---|

| Working voltage (V) | Creepage distance (mm) | | | | | | | Type of insulation | | | Verdict |
|---------------------|------------------------|----------------|------|-----------|----------------|-----|------------|--------------------|-----|-----|---------|
| | Pollution degree | | | | | | | | | | |
| | 1 | 2 | | | 3 | | | | | | |
| | | Material group | | | Material group | | | | | | |
| | | I | II | IIIa/IIIb | I | II | IIIa/IIIb* | B** | S** | R** | |
| ≤50 | 0,18 | 0,6 | 0,85 | 1,2 | 1,5 | 1,7 | 1,9 | | — | — | N/A |

| |
|-----------------------|
| IEC 60335-2-29 |
|-----------------------|

| 29.2 | TABLE: Creepage distances, basic, supplementary and reinforced insulation | | | | | | | | | | P |
|---------------------|---|------|-----------|----------------|------|------------|------|--------------------|-----|---------|-----|
| Working voltage (V) | Creepage distance (mm) Pollution degree | | | | | | | | | | |
| | 1 | 2 | | | 3 | | | Type of insulation | | | |
| | Material group | | | Material group | | | | | | | |
| | I | II | IIIa/IIIb | I | II | IIIa/IIIb* | B** | S** | R** | Verdict | |
| ≤50 | 0,18 | 0,6 | 0,85 | 1,2 | 1,5 | 1,7 | 1,9 | — | | — | N/A |
| ≤50 | 0,36 | 1,2 | 1,7 | 2,4 | 3,0 | 3,4 | 3,8 | — | — | | N/A |
| 125 | 0,28 | 0,75 | 1,05 | 1,5 | 1,9 | 2,1 | 2,4 | | — | — | N/A |
| 125 | 0,28 | 0,75 | 1,05 | 1,5 | 1,9 | 2,1 | 2,4 | — | | — | N/A |
| 125 | 0,56 | 1,5 | 2,1 | 3,0 | 3,8 | 4,2 | 4,8 | — | — | | N/A |
| 250 | 0,56 | 1,25 | 1,8 | 2,5 | 3,2 | 3,6 | 4,0 | 4.2 | — | — | N/A |
| 250 | 0,56 | 1,25 | 1,8 | 2,5 | 3,2 | 3,6 | 4,0 | — | 3.6 | — | N/A |
| 250 | 1,12 | 2,5 | 3,6 | 5,0 | 6,4 | 7,2 | 8,0 | — | — | 6.5 | N/A |
| 400 | 1,0 | 2,0 | 2,8 | 4,0 | 5,0 | 5,6 | 6,3 | | — | — | N/A |
| 400 | 1,0 | 2,0 | 2,8 | 4,0 | 5,0 | 5,6 | 6,3 | — | | — | N/A |
| 400 | 2,0 | 4,0 | 5,6 | 8,0 | 10,0 | 11,2 | 12,6 | — | — | | N/A |
| 500 | 1,3 | 2,5 | 3,6 | 5,0 | 6,3 | 7,1 | 8,0 | | — | — | N/A |
| 500 | 1,3 | 2,5 | 3,6 | 5,0 | 6,3 | 7,1 | 8,0 | — | | — | N/A |
| 500 | 2,6 | 5,0 | 7,2 | 10,0 | 12,6 | 14,2 | 16,0 | — | — | | N/A |
| >630 and ≤800 | 1,8 | 3,2 | 4,5 | 6,3 | 8,0 | 9,0 | 10,0 | | — | — | N/A |
| >630 and ≤800 | 1,8 | 3,2 | 4,5 | 6,3 | 8,0 | 9,0 | 10,0 | — | | — | N/A |
| >630 and ≤800 | 3,6 | 6,4 | 9,0 | 12,6 | 16,0 | 18,0 | 20,0 | — | — | | N/A |
| >800 and ≤1000 | 2,4 | 4,0 | 5,6 | 8,0 | 10,0 | 11,0 | 12,5 | | — | — | N/A |
| >800 and ≤1000 | 2,4 | 4,0 | 5,6 | 8,0 | 10,0 | 11,0 | 12,5 | — | | — | N/A |
| >800 and ≤1000 | 4,8 | 8,0 | 11,2 | 16,0 | 20,0 | 22,0 | 25,0 | — | — | | N/A |
| >1000 and ≤1250 | 3,2 | 5,0 | 7,1 | 10,0 | 12,5 | 14,0 | 16,0 | | — | — | N/A |
| >1000 and ≤1250 | 3,2 | 5,0 | 7,1 | 10,0 | 12,5 | 14,0 | 16,0 | — | | — | N/A |
| >1000 and ≤1250 | 6,4 | 10,0 | 14,2 | 20,0 | 25,0 | 28,0 | 32,0 | — | — | | N/A |
| >1250 and ≤1600 | 4,2 | 6,3 | 9,0 | 12,5 | 16,0 | 18,0 | 20,0 | | — | — | N/A |
| >1250 and ≤1600 | 4,2 | 6,3 | 9,0 | 12,5 | 16,0 | 18,0 | 20,0 | — | | — | N/A |

IEC 60335-2-29

| 29.2 | TABLE: Creepage distances, basic, supplementary and reinforced insulation | | | | | | | | | | | P |
|---------------------|---|----------------|-------|-----------|----------------|-------|------------|--------------------|-----|-----|-----|---------|
| Working voltage (V) | Creepage distance (mm) | | | | | | | | | | | Verdict |
| | Pollution degree | | | | | | | Type of insulation | | | | |
| | 1 | 2 | | | 3 | | | | | | | |
| | | Material group | | | Material group | | | | | | | |
| | | I | II | IIIa/IIIb | I | II | IIIa/IIIb* | B** | S** | R** | | |
| >1250 and ≤1600 | 8,4 | 12,6 | 18,0 | 25,0 | 32,0 | 36,0 | 40,0 | — | — | | N/A | |
| >1600 and ≤2000 | 5,6 | 8,0 | 11,0 | 16,0 | 20,0 | 22,0 | 25,0 | | — | — | N/A | |
| >1600 and ≤2000 | 5,6 | 8,0 | 11,0 | 16,0 | 20,0 | 22,0 | 25,0 | — | | — | N/A | |
| >1600 and ≤2000 | 11,2 | 16,0 | 22,0 | 32,0 | 40,0 | 44,0 | 50,0 | — | — | | N/A | |
| >2000 and ≤2500 | 7,5 | 10,0 | 14,0 | 20,0 | 25,0 | 28,0 | 32,0 | | — | — | N/A | |
| >2000 and ≤2500 | 7,5 | 10,0 | 14,0 | 20,0 | 25,0 | 28,0 | 32,0 | — | | — | N/A | |
| >2000 and ≤2500 | 15,0 | 20,0 | 28,0 | 40,0 | 50,0 | 56,0 | 64,0 | — | — | | N/A | |
| >2500 and ≤3200 | 10,0 | 12,5 | 18,0 | 25,0 | 32,0 | 36,0 | 40,0 | | — | — | N/A | |
| >2500 and ≤3200 | 10,0 | 12,5 | 18,0 | 25,0 | 32,0 | 36,0 | 40,0 | — | | — | N/A | |
| >2500 and ≤3200 | 20,0 | 25,0 | 36,0 | 50,0 | 64,0 | 72,0 | 80,0 | — | — | | N/A | |
| >3200 and ≤4000 | 12,5 | 16,0 | 22,0 | 32,0 | 40,0 | 45,0 | 50,0 | | — | — | N/A | |
| >3200 and ≤4000 | 12,5 | 16,0 | 22,0 | 32,0 | 40,0 | 45,0 | 50,0 | — | | — | N/A | |
| >3200 and ≤4000 | 25,0 | 32,0 | 44,0 | 64,0 | 80,0 | 90,0 | 100,0 | — | — | | N/A | |
| >4000 and ≤5000 | 16,0 | 20,0 | 28,0 | 40,0 | 50,0 | 56,0 | 63,0 | | — | — | N/A | |
| >4000 and ≤5000 | 16,0 | 20,0 | 28,0 | 40,0 | 50,0 | 56,0 | 63,0 | — | | — | N/A | |
| >4000 and ≤5000 | 32,0 | 40,0 | 56,0 | 80,0 | 100,0 | 112,0 | 126,0 | — | — | | N/A | |
| >5000 and ≤6300 | 20,0 | 25,0 | 36,0 | 50,0 | 63,0 | 71,0 | 80,0 | | — | — | N/A | |
| >5000 and ≤6300 | 20,0 | 25,0 | 36,0 | 50,0 | 63,0 | 71,0 | 80,0 | — | | — | N/A | |
| >5000 and ≤6300 | 40,0 | 50,0 | 72,0 | 100,0 | 126,0 | 142,0 | 160,0 | — | — | | N/A | |
| >6300 and ≤8000 | 25,0 | 32,0 | 45,0 | 63,0 | 80,0 | 90,0 | 100,0 | | — | — | N/A | |
| >6300 and ≤8000 | 25,0 | 32,0 | 45,0 | 63,0 | 80,0 | 90,0 | 100,0 | — | | — | N/A | |
| >6300 and ≤8000 | 50,0 | 64,0 | 90,0 | 126,0 | 160,0 | 180,0 | 200,0 | — | — | | N/A | |
| >8000 and ≤10000 | 32,0 | 40,0 | 56,0 | 80,0 | 100,0 | 110,0 | 125,0 | | — | — | N/A | |
| >8000 and ≤10000 | 32,0 | 40,0 | 56,0 | 80,0 | 100,0 | 110,0 | 125,0 | — | | — | N/A | |
| >8000 and ≤10000 | 64,0 | 80,0 | 112,0 | 160,0 | 200,0 | 220,0 | 250,0 | — | — | | N/A | |

IEC 60335-2-29

| 29.2 | TABLE: Creepage distances, basic, supplementary and reinforced insulation | | | | | | | | | | | P |
|---------------------|---|-------|-------|-----------|----------------|-------|------------|--------------------|-----|-----|-----|---------|
| Working voltage (V) | Creepage distance (mm) Pollution degree | | | | | | | | | | | Verdict |
| | 1 | 2 | | | 3 | | | Type of insulation | | | | |
| | Material group | | | | Material group | | | | | | | |
| | | I | II | IIIa/IIIb | I | II | IIIa/IIIb* | B** | S** | R** | | |
| >10000 and ≤12500 | 40,0 | 50,0 | 71,0 | 100,0 | 125,0 | 140,0 | 160,0 | | — | — | N/A | |
| >10000 and ≤12500 | 40,0 | 50,0 | 71,0 | 100,0 | 125,0 | 140,0 | 160,0 | — | | — | N/A | |
| >10000 and ≤12500 | 80,0 | 100,0 | 142,0 | 200,0 | 250,0 | 280,0 | 320,0 | — | — | | N/A | |

Supplementary information:

*) Material group IIIb is allowed if the working voltage does not exceed 50 V

**) B = Basic insulation, S = Supplementary insulation, R = Reinforced insulation

See table 29.1

| 29.2 | TABLE: Creepage distances, functional insulation | | | | | | | | P |
|---------------------|--|------|------|-------------------------|----------------|------|------------|------------------|---|
| Working voltage (V) | Creepage distance (mm) Pollution degree | | | | | | | | |
| | 1 | 2 | | | 3 | | | | |
| | Material group | | | | Material group | | | | |
| | | I | II | IIIa/IIIb | I | II | IIIa/IIIb* | Verdict / Remark | |
| ≤10 | 0,08 | 0,4 | 0,4 | 0,4 | 1,0 | 1,0 | 1,0 | N/A | |
| 50 | 0,16 | 0,56 | 0,8 | 1,1 | 1,4 | 1,6 | 1,8 | N/A | |
| 125 | 0,25 | 0,71 | 1,0 | 1,4 | 1,8 | 2,0 | 2,2 | N/A | |
| 250 | 0,42 | 1,0 | 1,4 | 2,0¹⁾ | 2,5 | 2,8 | 3,2 | P | |
| 400 | 0,75 | 1,6 | 2,2 | 3,2 | 4,0 | 4,5 | 5,0 | N/A | |
| 500 | 1,0 | 2,0 | 2,8 | 4,0 | 5,0 | 5,6 | 6,3 | N/A | |
| >630 and ≤800 | 1,8 | 3,2 | 4,5 | 6,3 | 8,0 | 9,0 | 10,0 | N/A | |
| >800 and ≤1000 | 2,4 | 4,0 | 5,6 | 8,0 | 10,0 | 11,0 | 12,5 | N/A | |
| >1000 and ≤1250 | 3,2 | 5,0 | 7,1 | 10,0 | 12,5 | 14,0 | 16,0 | N/A | |
| >1250 and ≤1600 | 4,2 | 6,3 | 9,0 | 12,5 | 16,0 | 18,0 | 20,0 | N/A | |
| >1600 and ≤2000 | 5,6 | 8,0 | 11,0 | 16,0 | 20,0 | 22,0 | 25,0 | N/A | |
| >2000 and ≤2500 | 7,5 | 10,0 | 14,0 | 20,0 | 25,0 | 28,0 | 32,0 | N/A | |

IEC 60335-2-29

| | | | | | | | | |
|-------------------|------|------|------|-------|-------|-------|-------|-----|
| >2500 and ≤3200 | 10,0 | 12,5 | 18,0 | 25,0 | 32,0 | 36,0 | 40,0 | N/A |
| >3200 and ≤4000 | 12,5 | 16,0 | 22,0 | 32,0 | 40,0 | 45,0 | 50,0 | N/A |
| >4000 and ≤5000 | 16,0 | 20,0 | 28,0 | 40,0 | 50,0 | 56,0 | 63,0 | N/A |
| >5000 and ≤6300 | 20,0 | 25,0 | 36,0 | 50,0 | 63,0 | 71,0 | 80,0 | N/A |
| >6300 and ≤8000 | 25,0 | 32,0 | 45,0 | 63,0 | 80,0 | 90,0 | 100,0 | N/A |
| >8000 and ≤10000 | 32,0 | 40,0 | 56,0 | 80,0 | 100,0 | 110,0 | 125,0 | N/A |
| >10000 and ≤12500 | 40,0 | 50,0 | 71,0 | 100,0 | 125,0 | 140,0 | 160,0 | N/A |

Supplementary information:

*) Material group IIIb is allowed if the working voltage does not exceed 50 V

Remark: 1) L/N in front of current fuse:Cr=2.6mm.

IEC 60335-2-29

| 30 | | | | | | | | | | | | | | | | | | | | TABLE: Resistance to heat and fire | | | | | | | | | | | | | | | | | | | |
|-----------------------|--------------------------------|----------------|--------------------------|-----------|-----------------|---------------|-------------------------------|-----|----------------|-----|----|-----|---|-----|-----|-----|---|-----|-----------------------------------|------------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Object/ part No. | Manufactur er/ trademark | Type/ model | Ball pressure test °C | | | | Glow wire test (GWT) °C | | | | | | Glow-wire flammability index (GWFI) °C | | | | Glow-wire ignition temp. (GWIT) °C | | Needle- flame test (NFT) | Verdict | | | | | | | | | | | | | | | | | | | |
| | | | 75 | 125 | cl. 11 +40 | cl. 19 +25 | 550 | 650 | | 750 | | 850 | 550 | 650 | 750 | 850 | 675 | 775 | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | t _e | | t _i | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Transformer bobbin | See 24.1 | See 24.1 | -- | 1.1 mm | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |
| Plastic of inlet | See 24.1 | See 24.1 | -- | 1.1 mm | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |
| Connector | See 24.1 | See 24.1 | -- | 1.1 mm | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |
| Enclosure plastic | See 24.1 | See 24.1 | -- | | 90 1.2m m | -- | P | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |
| PCB | See 24.1 | CCEM-1 | -- | 0.7 mm | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |
| PCB | See 24.1 | CY-10 | -- | 0.7 | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P | | | | | | | | | | | | | | | | | | | |

| |
|-----------------------|
| IEC 60335-2-29 |
|-----------------------|

| | | | | mm | | | | | | | | | | | | | | | | |
|---------------------------------------|-------------------|----------|----|-----------|----|----|----|----|----|---|---|---|----|----|----|----|----|----|----|---|
| Coil bobbin | See 24.1 | See 24.1 | -- | 1.4 mm | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P |
| Transformer tape | See 24.1 | See 24.1 | -- | -- | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P |
| X2 capacitor | Tenta Electric | MEX | -- | -- | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P |
| X2 capacitor | Farad Electronics | PXK | -- | -- | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P |
| Output plastic of terminal connection | See 24.1 | See 24.1 | -- | -- | -- | -- | -- | -- | -- | 0 | 0 | P | -- | -- | -- | -- | -- | -- | -- | P |

Supplementary information:

- 1) Parts of material classified at least HB40 or if relevant HBF
- 2) Parts of material classified as V-0 or V-1
- 3) Flame persisting longer than 2 s (= t_e – t_i) need only be reported for unattended appliances
- 4) Surrounding parts subjected to the needle-flame test of annex E
- 5) Base material classified as V-0 or if relevant VTM-0
- 6) The GWIT pre-selection option, the 850 °C GWFI pre-selection option, and the 850 °C GWT are not applicable for attended appliances

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

**ATTACHMENT TO TEST REPORT IEC 60335-2-29
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES**

Safety of household and similar electrical appliances
Part 2: Particular requirements for battery chargers

| | |
|--|--|
| Differences according to: | EN 60335-2-29:2004 + A2:2010 used in conjunction with EN 60335-1:2012+A11:2014 EN 62233:2008 |
| Attachment Form No.: | EU_GD_IEC60335_2_29I |
| Attachment Originator: | SIQ |
| Master Attachment: | 2013-04 |
| Copyright © 2013 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved. | |

| CENELEC COMMON MODIFICATIONS | | | |
|-------------------------------------|---|--|-----|
| 6.1 | Delete "class 0" and "class 01" | | P |
| 7.1 | Single-phase appliances to be connected to the supply mains: 230 V covered | | P |
| | Multi-phase appliances to be connected to the supply mains: 400 V covered | | N/A |
| 7.10 | Devices used to start/stop operational functions of the appliance distinguished from other manual devices by means of shape, size, surface texture, position, etc. | | P |
| | An indication that the device has been operated is given by: | | P |
| | • a tactile feedback, or | | N/A |
| | • an audible and visual feedback | | P |
| 7.12 | The instructions include the substance of the following: | | P |
| | - this appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved | | P |
| | - children shall not play with the appliance | | P |
| | - cleaning and user maintenance shall not be made by children without supervision | | P |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 7.12.Z1 | The specific instructions related to the safe operation of this appliance is collated together in the front section of the user instructions | | P |
| | The height of the characters, measured on the capital letters, is at least 3 mm | | P |
| | These instructions are also available in an alternative format, e.g. on a website | | P |
| 8.1.1 | Also test probe 18 of EN 61032 is applied | | P |
| | The appliance being in every possible position during the test | | P |
| | The force on the probe in the straight position is increased to 10 N when probe 18 is used | | P |
| | When using test probe 18 the appliance is fully assembled as in normal use without any parts removed, and | | P |
| | parts intended to be removed for user maintenance are also not removed | | P |
| 8.2 | Compliance is checked by applying the test probes of EN 61032 | | P |
| | For built-in appliances and fixed appliances, the test probe B and probe 18 of EN 61032 are applied only after installation | | N/A |
| 11.8 | Footnotes to "External enclosure of motor-operated appliances" to be taken into account | | P |
| 15.1.2 | Appliances with an automatic cord reel tested with the cord in the most unfavourable position so that the reeling of the wet cord may affect electrical insulation during operation, the cord not being dried before reeling | | N/A |
| 20.2 | When using the test probe similar to test probe B with a circular stop face, the accessories and detachable covers are removed | | P |
| | Test probe 18 applied with a force of 2,5N on the appliance fully assembled | | P |
| 24.1 | Components comply with the safety requirements specified in the relevant standards as far as they reasonably apply | | P |
| | The requirements of Clause 29 of this standard apply between live parts of components and accessible parts of the appliance. | | P |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The requirements of 30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components | | P |
| | Components that have not been previously tested or do not comply with the standard for the relevant component are tested according to the requirements of 30.2 | | P |
| | Components that have been previously tested and shown to comply with the resistance to fire requirements in the standard for the relevant component need not be retested provided that: | | P |
| | - the severity specified in the component standard is not less than the severity specified in 30.2, and | | P |
| | - the test report for the component states whether it complied with the standard for the relevant component with or without flame, flames not exceeding 2 s during the test are ignored | | P |
| | Unless components have been previously tested and found to comply with the relevant standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9 | | P |
| | For components mentioned in 24.1.1 to 24.1.9, no additional tests specified in the relevant standard for the component are necessary other than those specified in 24.1.1 to 24.1.9 | | P |
| | Components that have not been separately tested and found to comply with the relevant standard, and | | P |
| | components that are not marked or not used in accordance with their marking, | | P |
| | are tested in accordance with the conditions occurring in the appliance, the number of samples being that required by the relevant standard | | P |
| | Lamp holders and starter holders that have not been previously tested and found to comply with the relevant standard are tested as a part of the appliance and additionally comply with the gauging and interchangeability requirements of the relevant standard under the conditions occurring in the appliance | | N/A |
| | Where the relevant standard specifies these gauging and interchangeability requirements at elevated temperatures, the temperatures measured during the tests of Clause 11 are used | | P |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Plugs and socket-outlets and other connecting devices of interconnection cords are not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1, or | | P |
| | with connectors and appliance inlets complying with the standard sheets of IEC 60320-1, | | P |
| | if direct supply to these parts from the supply mains gives rise to a hazard | | P |
| 24.1.7 | If the remote operation of the appliance is via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is EN 41003 | | N/A |
| | Compliance with Clause 8 of this standard is not impaired by connecting the appliance to a device covered by EN 41003 | | N/A |
| 24.Z1 | For motor running capacitors (IEC 60252-1 type P2) with a metallic enclosure having an overpressure fuse the flame testing of internal plastic parts supporting current carrying connections as required in 30.2.2 and 30.2.3.1 is not necessary | | N/A |
| 25.6 | Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC/TR 60083: | | P |
| | - for Class I appliances: standard sheet C2b, C3b or C4.....: | See table 24.1 | P |
| | - for Class II appliances: standard sheet C5 or C6 | | N/A |
| 25.7 | Rubber sheathed cords (60245 IEC 53) are not suitable for appliances intended to be used outdoors or when they are liable to be exposed to significant amount of ultraviolet radiation | | N/A |
| | Halogen-free thermoplastic compound sheathed supply cords have properties at least those of: | | N/A |
| | <ul style="list-style-type: none"> halogen-free thermoplastic compound sheathed cords (H03Z1Z1H2-F or H03Z1Z1-F), for appliances having a mass not exceeding 3 kg | | N/A |
| | <ul style="list-style-type: none"> halogen-free thermoplastic compound sheathed cords (H05Z1Z1H2-F or H05Z1Z1-F), for other appliances | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Cross-linked halogen-free compound sheathed supply cords have properties at least those of cross-linked halogen-free compound sheathed cords (H07ZZ-F) | | N/A |
| 26.11 | Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain them in position unless they are held in place near the terminals independently of the solder | | N/A |
| 29.3.Z1 | Appliance constructed so that if there is a possibility of damaging the insulation during installation, the insulation withstands the scratch and penetration test of 21.2 | | N/A |
| 32 | Compliance regarding electromagnetic fields is checked according to EN 62233 | | P |
| Annex I, 19.1.101 | The appliance is supplied at rated voltage and operated under normal operation with each of the fault conditions specified | | N/A |
| | The duration of the test is as specified in 19.7 | | N/A |

| | | | |
|----------------|---|--|-----|
| ZA | ANNEX ZA (NORMATIVE) SPECIAL NATIONAL CONDITIONS | | P |
| | Norway | | N/A |
| 19.5 | The test is also applicable to appliances intended to be permanently connected to fixed wiring | | N/A |
| | Norway | | N/A |
| 22.2 | The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system | | N/A |
| | All CENELEC countries | | P |
| 25.6 and 25.25 | Information concerning National plug and socket-outlets is available from the CENELEC website. Normative national requirements concerning plug and socket-outlets are shown in the relevant National standard | | P |
| | Ireland and United Kingdom | | N/A |
| 25.8 | In the table, the lines for 10 A and 16 A are replaced by: | | N/A |
| | > 10 and ≤ 13 1,25 | | N/A |
| | > 13 and ≤ 16 1,5 | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| ZB | ANNEX ZB (INFORMATIVE) A-DEVIATIONS | | N/A |
| | Ireland | | N/A |
| 25.6 | These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs complying with I.S. 401:1997, or equivalent, to be fitted to domestic appliances | | N/A |
| | United Kingdom | | N/A |
| 25.6 | These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs to BS 1363 to be fitted to domestic appliances. It also allows plugs to BS 4573 and EN 50075 to be fitted to shavers and toothbrushes | | N/A |
| ZC | ANNEX ZC (NORMATIVE) NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS | | N/A |
| | A list of referenced documents in this standard | | N/A |
| ZD | ANNEX ZD (INFORMATIVE) IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS | | P |
| | A table with IEC and CENELEC code designations for flexible cords | | P |
| ZE | ANNEX ZE (INFORMATIVE) SPECIFIC ADDITIONAL REQUIREMENTS FOR APPLIANCES AND MACHINES INTENDED FOR COMMERCIAL USE | | N/A |
| 7.1 | Business name and full address of the manufacturer and, where applicable, his authorized representative.....: | | N/A |
| | Model or type reference.....: | | N/A |
| | Serial number, if any.....: | | N/A |
| | Production year | | N/A |
| | Designation of the appliance | | N/A |
| 7.12 | Instructions provided with the appliance so that the appliance can be used safely | | N/A |
| | The instructions contain at least the following information: | | N/A |
| | - the business name and full address of the manufacturer and, where applicable, his authorized representative | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | - model or type reference of the appliance as marked on the appliance itself, except for the serial number | | N/A |
| | - the designation of the appliance together with its explanation in case it is given by a combination of letters and/or numbers | | N/A |
| | - the general description of the appliance, when needed due to the complexity of the appliance | | N/A |
| | - specific precautions if required during installation, operation, adjusting, user maintenance, cleaning, repairing or moving | | N/A |
| | - when needed drawings, diagrams, descriptions and explanations necessary for the safe use and user maintenance of the appliance | | N/A |
| | - the possible reasonably foreseeable misuse and, whenever relevant, a warning against the effects it may have on the safe use of the appliance | | N/A |
| | The words "Original instructions" appear on the language version(s) verified by the manufacturer or by the authorized representative | | N/A |
| | When a translation of the original instructions has been provided by a person introducing the appliance on the market; the meaning of the sentence "Translation of the original instructions" appear in the relevant instructions delivered with the appliance | | N/A |
| | The instructions for maintenance/service to be done by specialized personnel, mandated by the manufacturer or the authorized representative may be supplied in only one Community language which the specialized personnel understand | | N/A |
| | The instructions indicate the type and frequency of inspections and maintenance required for safe operation including the preventive maintenance measures | | N/A |
| 7.12.ZE1 | If needed for specific appliances, the following information to be given: | | N/A |
| | <ul style="list-style-type: none"> on use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns, if these operations have consequences on stability of the appliance in order to avoid overturning, falling or uncontrolled movements of the appliance or of its component parts | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | <ul style="list-style-type: none"> on how to maintain adequate mechanical stability when in use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance | | N/A |
| | <ul style="list-style-type: none"> on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided | | N/A |
| | <ul style="list-style-type: none"> on the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur the operating method to safely unblock the appliance | | N/A |
| | <ul style="list-style-type: none"> on the specifications on the spare parts to be used, when these affect the health and safety of the operator | | N/A |
| | <ul style="list-style-type: none"> on airborne noise emissions, determined and declared in accordance with the relevant Part 2, which includes: | | N/A |
| | <ul style="list-style-type: none"> - the A-weighted emission sound pressure level at workstations, where this exceeds 70 dB(A) | | N/A |
| | <ul style="list-style-type: none"> - where this level does not exceed 70 dB(A), this fact is indicated | | N/A |
| | <ul style="list-style-type: none"> - the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 dB in relation to 20 µPa)..... | | N/A |
| | <ul style="list-style-type: none"> - the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 dB(A)..... | | N/A |
| 7.12.ZE2 | The instructions includes a warning to disconnect the appliance from its power source during service and when replacing parts | | N/A |
| | If the removal of the plug is foreseen, it is clearly indicated that the removal of the plug has to be such that an operator can check from any of the points to which he has access that the plug remains removed | | N/A |
| | If this is not possible, due to the construction of the appliance or its installation, a disconnection with a locking system in the isolated position is provided | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 19.11.4.8 | The appliance continues to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage fluctuation occurred, or | | N/A |
| | a manual operation is required to restart it | | N/A |
| 20.1 | Appliances and their components and fittings have adequate mechanical stability during transportation, assembly, dismantling and any other action involving the appliance | | N/A |
| 20.2 | Dangerous moving transmission parts safeguarded either by design or guards | | N/A |
| | When guards are used, they are fixed guards, interlocking movable guards or protective devices | | N/A |
| | Moving parts directly involved in the function of the appliance which cannot be made completely inaccessible fitted with: | | N/A |
| | - fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and | | N/A |
| | - adjustable guards restricting access to those sections of the moving parts where access is necessary | | N/A |
| | Interlocking movable guards used where frequent access is required | | N/A |
| 21.1 | Appliances and their components and fittings have adequate mechanical strength and is constructed to withstand such rough handling that may be expected in normal use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance | | N/A |
| 22.ZE.1 | For appliances provided with a seat, the seat gives adequate stability | | N/A |
| | The distance between the seat and the control devices capable of being adapted to the operator | | N/A |
| 22.ZE.2 | For appliances provided with separate devices for the start and the stop functions, the stop function is unambiguously identifiable and does always override the start function | | N/A |
| | For appliances provided with one device performing the start and the stop function, the stop function is unambiguously identifiable and does always override the start function | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 22.ZE.3 | Appliances designed in such a way that incorrect mounting is avoided, if this can lead to an unsafe situation | | N/A |
| | If this is not possible, information on the correct mounting is given directly on the part and/or the enclosure | | N/A |
| 22.ZE.4 | Where the weight, size or shape prevents appliances from being moved manually, they are fitted with attachments for lifting gear, or | | N/A |
| | so designed that they can be fitted with such attachments, or | | N/A |
| | be shaped in such a way that standard lifting gear can easily be used | | N/A |
| | Appliances to be moved manually are constructed or equipped so that they can be moved easily and safely | | N/A |
| 22.ZE.5 | The fixing systems of fixed guards which prevent access to dangerous moving transmission parts only removable with the use of tools | | N/A |
| | If such guards have to be removed by the user for routine cleaning or maintenance their fixing systems remain attached to the fixed guards or to the machine after removal | | N/A |
| | Where possible, guards are incapable of remaining in place without their fixings | | N/A |
| | This does not apply if, after removal of the screws, or if the component is incorrectly repositioned, the appliance becomes inoperative | | N/A |
| | Movable guards are interlocked | | N/A |
| | The interlocking devices prevent the start of hazardous appliance functions until the guards are fixed in their position, and give a stop command whenever they are no longer closed | | N/A |
| | Where it is possible for an operator to reach the danger zone before the risk due to hazardous appliance functions has ceased, movable guards associated with a guard locking device in addition to an interlocking device that: | | N/A |
| | - prevents the start of hazardous appliance functions until the guard is closed and locked, and | | N/A |
| | - keeps the guard closed and locked until the risk of injury from the hazardous appliance functions has ceased | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Interlocking movable guards remain attached to the appliance when open, and | | N/A |
| | they are designed and constructed in such a way that they can be adjusted only by means of an intentional action | | N/A |
| 22.ZE.6 | Interlocking movable guards designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous appliance functions | | N/A |
| | The guard is opened to the extent needed to cause the interlocking to operate and is then closed, the number of operations being defined in the specific Part 2 | | N/A |
| | After this test any defect that may be expected in normal use is applied to the interlock system, including interruption of the supply, only one defect being simulated at a time | | N/A |
| | After these tests the interlock system is fit for further use | | N/A |
| 22.ZE.7 | Adjustable guards restricting access to areas of the moving parts strictly necessary for the work are: | | N/A |
| | - adjustable manually or automatically, depending on the type of work involved, and | | N/A |
| | - readily adjustable without the use of tools | | N/A |
| 22.ZE.8 | In case of interruption, re-establishment after an interruption or fluctuation in whatever manner of the power supply, the appliance does not restart | | N/A |
| | However, automatic restarting of the operation is allowed if the appliance may continue to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage interruption or fluctuation occurred | | N/A |
| 22.ZE.9 | Appliances fitted with means to isolate them from all energy sources | | N/A |
| | Such isolators are clearly identified, and | | N/A |
| | they are capable of being locked if reconnection endanger persons | | N/A |
| | After the energy source is disconnected, it is possible to dissipate any energy remaining or stored in the circuits of the appliance without risk to persons | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| ZF | ANNEX ZF (INFORMATIVE) CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD | | P |
| | List of standards under CENELEC/TC61 with the allocation under the LVD (Low Voltage Directive) or the MD (Machinery Directive) | LVD | P |
| ZG | ANNEX ZG (NORMATIVE) UV APPLIANCES | | N/A |
| | The following modifications to this standard apply to appliances having UV emitters | | N/A |
| | This annex is not applicable to appliances covered by the scopes of IEC 60335-2-27, IEC 60335-2-59 or IEC 60335-2-109 | | N/A |
| 7.12.ZG | The instructions for appliances incorporating UVC emitters include the substance of the following: WARNING — This appliance contains a UV emitter. Do not stare at the light source | | N/A |
| 32 | For appliances incorporating UV emitters the manufacturer delivers a declaration providing evidence that the plastic material exposed to the radiation is UV resistant | | N/A |
| ZZ | ANNEX ZZ (INFORMATIVE) COVERAGE OF ESSENTIAL REQUIREMENTS OF EC DIRECTIVES | | P |
| | Description of the relation between this European standard and the LVD (Low Voltage Directive, 2006/95/EC) and the MD (Machinery Directive, 2006/42/EC) | LVD | P |

| EN 60335-1: 2012/A11: 2014 | | | |
|----------------------------|--|--|-----|
| 7 | MARKING AND INSTRUCTIONS (EN 60335-1/A11) | | P |
| 7.1 | (Replacement: In NOTE Z1, replace "IEC 82079-1" by "EN 82079-1". | | N/A |
| ZF | ANNEX ZF (INFORMATIVE) CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD(EN 60335-1/A11) | | N/A |

| IEC60335_2_29I - ATTACHMENT | | | |
|-----------------------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | (Replacement: In Table ZF.1 – List of standards under CLC/TC 61, replace line of EN 60335-2-38 | | N/A |

| Annex EN 62233:2008 | | | |
|-------------------------------------|---|-----------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| EMF- ELECTROMAGNETICS FIELDS | | | |
| | The tested product also complies with the requirements of EN 62233:2008 | | P |
| | Limit100% | Measured max. :1.235% | P |

-- End of test report --

Annex 2: Information from GS test center

Material list for PAH risk assessment; Only materials accessible without tools

Product designation: Li-ion Battery Charger Model: SSLC084V42J, SSLC058V29J

Certificate No.: S50335151 0001

Test report No.: 16072518 001

For PAH relevant material/components only!


| Material / Component # | Location / Function of the material | Name / Description of the material | PAH relevant 1) | Evidence attached. Institute, report no., date | Category | Smell | Rigidity | Colour | Correction of data by test center? 1) | Chem. test needed? | Test result (within the given limits) | Attachement |
|------------------------|-------------------------------------|------------------------------------|--|--|---|--|---|--|--|--|---|----------------------------------|
| 1 | Plastic enclosure | Black plastic | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No | TUV SUD report No. 68.167.15.0690.01 Dated 2015-12-01 | <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | <input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid | <input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored | <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes | <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes | <input checked="" type="checkbox"/> passed <input type="checkbox"/> failed | TUV SUD report 68.167.15.0690.01 |
| 2 | Foot | Black soft plastic | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No | TUV SUD report No. 68.167.15.0690.01 Dated 2015-12-01 | <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 | <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | <input checked="" type="checkbox"/> Soft <input type="checkbox"/> Flexible <input type="checkbox"/> Rigid | <input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored | <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes | <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes | <input checked="" type="checkbox"/> passed <input type="checkbox"/> failed | TUV SUD report 68.167.15.0690.01 |

1) Please fill out the table only if the general risk assessment indicates PAH relevance

2) Applicant data from Annex 1

Assessed by *name*

Place TÜV Rheinland (Guangdong) Ltd., Date 2016.03.23

Johnny Cao
(Test engineers signature) 

Risk assessment for the above mentioned product indicates PAH relevance :

Yes ¹⁾

No

Short statement

AfPS GS 2014:01 considered, all relevant materials listed.
Product complies to AfPS GS 2014:01